

Terminals, I-Series

Terminals, I-Series	Overview I-Series	C.2
	Feed-through terminals	C.6
	Modular PE terminals	C.10
	Double level terminals	C.14
	Modular disconnect terminals	C.18
	Fuse terminals	C.20
	Hybrid modular terminals	C.22
	Pluggable standard terminals	C.30
	Initiator and actuator terminals	C.32
	Terminals with electronic components	C.38
	Accessories I-Series	C.42

I-Series / IDC technology



IDC stands for Insulation Displacement Connection. Innovative, more effective, offering greater cost-savings and maximum contact reliability.

This method of connection, already tried and tested in telecommunications and electronics, is now available for industrial applications incorporated into modular terminals.

The IDC technology results in minimum work during installation but still guarantees reliable contact – and all **without special cable preparation tools, the associated time or cost.**


All standardised PVC-insulated conductors with cross-sections between 0.21 and 1.5 mm² (0.5 and 2.5 mm²) are suitable for this type of connection.

Users who wish to connect special conductors should consult Weidmüller first. For all up-to-date information about this

type of connection simply visit the website at **www.idc2.de**.

If it is not possible to connect a certain type of conductor, the Weidmüller hybrid

terminals, could offer the best solution. These terminals have an IDC on one side and either a screw or tension clamp connection on the other.



Product overview

Rated cross-section	1.5 mm²	2.5 mm²
Feed-through terminals		
2 connections	•	•
3 connections	•	•
4 connections	•	•
PE terminals		
2 connections	•	•
3 connections	•	•
4 connections	•	•
Fuse terminals	•	•
Disconnect terminals	•	•
Double level terminals	•	
Initiator/Actuator terminals	•	
Plug-in terminals	•	
Hybrid terminals (IDC/screw)		
2 connections	•	•
3 connections	•	•
Hybrid terminals (IDC/tension clamp)		
2 connections	•	•
3 connections	•	
Terminals with electrical components	•	•

1 The connection

Separating the electrical and mechanical functions (galvanic isolation) results in major advantages for this type of connection, too.

- Extremely high contact reliability thanks to the extra spring (spring steel).
- Copper current bar for low through resistance..
- A wide clamping range for different cross-sections: 0.21...1.5 mm² and 0.50...2.5 mm²

2 Plug-in cross-connections

- 2- to 10-pole, or "endless" for custom fabrication.
- Full rated current.
- Break-out poles for bypassing alternate potentials.
- Electric shock protection (finger-proof) to German standard VBG 4.

3 Maximum ease of use

Insert the screwdriver as far as possible into the clamping point, press sideways, and the connection is complete!


A visible, reliable connection.

**The Wemid insulating material**


- Non-tracking, CTI 600
- Thermally stable up to 120°C
- V0 flammability rating to UL 94
- Free from halogen and phosphor flame-retardant substances

Major time- and cost-savings

- Time-savings of up to 76% compared with conventional types of connection (see next page)

**4 Reliable contact**

- Reliable contact thanks to the visual check

**Comprehensive accessories**

- Test adapter, test plug
- Can be used with standard and group markers
- End plates, partition plates
- Covers
- Reducing sleeves
- Fuse holder

**Standards and directives**


IDC2 terminals comply with standards such as:

- Modular terminal standards: IEC 60947-7-1/-2/-3
- IDC standard: IEC 60352-4
- More stringent Weidmüller tests
- National and international approvals, Germanischer Lloyd, Lloyds Register, DNV, RINA, KEMA, KEUR
- ATEX approval



How it works


No stripping – no crimping – no special tools



Insert the cut-off conductor straight into the terminal ...



... then insert the screwdriver as far as it will go in front of the slide.



Now press the slide using the screwdriver so that it engages.

Pull the screwdriver out: the conductor is securely in place. Without stripping or crimping ferrules, without the need for any special tools.

A look inside ...

shows the benefits of our technology.

Conductor being cut:


the insulation is pre-cut.

Conductor during wiring:

the insulation is cut through, producing the first contact with the current bar.

Conductor in its final position:

the insulation is cut through completely, ensuring secure contact over a wide area.




The benefits: Extreme time-savings

In comparison:
Clamping yoke

Tension clamp


IDC2



Quick connection ...
secure contact

Connecting with convincing results: practical tests have shown that users can achieve time-savings of up to 76 % compared to other connection techniques. The high-speed connection and more secure contact are produced without any additional tools.

Secure connection with visual function check



The yellow sliding mechanism shows you at a glance whether the conductor is properly in contact

Separately sprung

The tensioned steel IDC contact ensures galvanic isolation. This principle offers a high degree of safety and flexibility when connecting up different conductor cross-sections.




IDU 1.5N/4AN

1.5 mm²

5.1 x 93.5 x 40.5

/ 1.5

0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4

Ex e II  II 2 G D

IEC	UL	CSA	EN 60079-7
500	300	300	275
17.5	10	10	15
1.5	AWG 24... 16	AWG 24... 16	1.5
6 / 3			
/ V-0			



KEMA 02ATEX2241 U

Rated connection	further connection
0.21...1.5	
0.21...1.5	

/ 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5


IDU 1.5N/2X2AN

1.5 mm²

5.1 x 93.5 x 40.5

/ 1.5

0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4

Ex e II  II 2 G D

IEC	UL	CSA	EN 60079-7
500			275
17.5			
1.5	AWG 24... 16	AWG 24... 16	1.5
6 / 3			
/ V-0			



KEMA 02ATEX2241 U

Rated connection	further connection
0.21...1.5	
0.21...1.5	

/ 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

Type	Qty.	Order No.
IDU 1.5N/4AN	100	1792600000
IDU 1.5N/4AN BL	100	1792610000

Type	Qty.	Order No.
IDU 1.5N/2X2AN	100	1824340000

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000

width [mm]			
IAP 1.5N/4AN	2	50	1792470000
IAP 1.5N/4AN BL	2	50	1792480000

width [mm]			
WEW-35/2	8	100	1061200000

ITA 1	25	1803800000
ITA 1/ZA	25	1803810000

SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

IRH 1.5	100	1804510000
---------	-----	------------

IAD 1/4 GE MIT BLITZ	20	1805500000
IAD 1/4 GE Neutral	20	1818420000

WS 10/5

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000

width [mm]			
IAP 1.5N/4AN	2	50	1792470000
IAP 1.5N/4AN BL	2	50	1792480000

width [mm]			
WEW-35/2	8	100	1061200000

ITA 1	25	1803800000
ITA 1/ZA	25	1803810000

SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

IRH 1.5	100	1804510000
---------	-----	------------

IAD 1/4 GE MIT BLITZ	20	1805500000
IAD 1/4 GE Neutral	20	1818420000

WS 10/5


IDU 2.5N/4AN

2.5 mm²

6.1 x 105.9 x 45.6

/ 2.5

0.5 ... 2.5



IEC 60947-7-1 / IEC 60352-4

Ex e II



II 2 G D

IEC	UL	CSA	EN 60079-7
800	600	600	550
24	15	15	21
2.5	AWG 20... 14	AWG 20... 14	2.5
8 / 3			
/ V-0			



DEMKO 03ATEX134054U

Rated connection	further connection
0.5...2.5	
0.5...2.5	

/ 0.6 x 3.5


IDU 2.5N/2x2AN

2.5 mm²

6.1 x 105.9 x 45.6

/ 2.5

0.5 ... 2.5



IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
800	600	600	
24	15	15	
2.5	AWG 20... 14	AWG 20... 14	
8 / 3			
/ V-0			



Rated connection	further connection
0.5...2.5	
0.5...2.5	

/ 0.6 x 3.5

Type	Qty.	Order No.
IDU 2.5N/4AN	50	1812960000
IDU 2.5N/4AN BL	50	1812970000

Type	Qty.	Order No.
IDU 2.5N/2x2AN	50	1821230000

Type	Current [A]	Qty.	Order No.
ZQV 4/2 GE	32	60	1608950000
ZQV 4/3 GE	32	60	1608960000
ZQV 4/4 GE	32	60	1608970000
ZQV 4/10 GE	32	20	1609030000
ZQV 4/20 GE	32	20	1909010000

width [mm]			
IAP 2.5N/4AN	2	50	1813070000
IAP 2.5N/4AN BL	2	50	1813080000

width [mm]			
WEW-35/2	8	100	1061200000

ITA 2	25	1821210000
ITA 2/ZA	25	1821220000

SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

IRH 2.5	100	1848230000
---------	-----	------------

IAD 2/4 GE MIT BLITZ	20	1828420000
IAD 2/4 GE NEUTRAL	20	1828430000

WS 10/6

Type	Current [A]	Qty.	Order No.
ZQV 4/2 GE	32	60	1608950000
ZQV 4/3 GE	32	60	1608960000
ZQV 4/4 GE	32	60	1608970000
ZQV 4/10 GE	32	20	1609030000
ZQV 4/20 GE	32	20	1909010000

width [mm]			
IAP 2.5N/4AN	2	50	1813070000
IAP 2.5N/4AN BL	2	50	1813080000

width [mm]			
WEW-35/2	8	100	1061200000

ITA 2	25	1821210000
ITA 2/ZA	25	1821220000

SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

IRH 2.5	100	1848230000
---------	-----	------------

IAD 2/4 GE MIT BLITZ	20	1828420000
IAD 2/4 GE NEUTRAL	20	1828430000

WS 10/6

Modular PE terminals

When using ATEX certified components in hazardous area applications the installation instructions and the rated data for accessories in the technical appendix must be considered.

width x length x height with TS 35 x 7.5 mm
 max. current / max. cond. cross-section A/mm²
 max. clamping range mm²

Technical data

Rated data	
Rated cross-section	mm ²
Rated voltage to adjacent terminal	V
Rated impulse withstand voltage to adjacent terminal	kV
Short-time withstand current	A
Pollution severity	
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	

Clamped conductors (H05V/H07V)

Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Tightening torque range (clamping screw)	Nm
Tightening torque range (fixing screw)	Nm
Stripping length / Blade size	mm / -

2 clamped cables with same cross-section (H05V/H07V)

Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²

Note

Ordering data

Version
green/yellow Wemid

Note

Accessories

End plate
dark beige Wemid

End bracket
dark beige / beige

Testing / Checking

For testing wired terminal strips	Standard
	with spigot

Screwdrivers

with cutting device "swifty set"	
Standard	

Reducing sleeves

for conductors < 0.5 mm ² / < AWG 20	
for conductors < 1.0 mm ² / < AWG 18	


PEN jumper

Inserted into TN-S distributor between N and PE terminals


Marking systems	(see large assortment in catalogue 7)
	Marking tags

For detailed information on other accessories and applications see "Accessories"

IPE 1.5N

1.5 mm²

5.1 x 59.5 x 40.5
 / **1.5**
0.21 ... 1.5



IEC 60947-7-2 / IEC 60352-4 Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
1.5	AWG 24... 16	AWG 24... 16	1.5
500			
6			
3			
/ V-0			

KEMA 02ATEX2241 U


Rated connection	further connection
0.21...1.5	
0.21...1.5	
/ 0.6 x 3.5	

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

IPE 1.5N/3AN

1.5 mm²

5.1 x 78.5 x 40.5
 / **1.5**
0.21 ... 1.5



IEC 60947-7-2 / IEC 60352-4 Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
1.5	AWG 24... 16	AWG 24... 16	1.5
500			
6			
3			
/ V-0			

KEMA 02ATEX2241 U

Rated connection	further connection
0.21...1.5	
0.21...1.5	
/ 0.6 x 3.5	

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

Type	Qty.	Order No.
IPE 1.5N	100	1792560000

Type	Qty.	Order No.
IPE 1.5N/3AN	100	1792590000

Type	width [mm]	Qty.	Order No.
IAP 1.5N	2	50	1792430000

Type	width [mm]	Qty.	Order No.
IAP 1.5N/3AN	2	50	1792450000

Type	width [mm]	Qty.	Order No.
WEW-35/2	8	100	1061200000

Type	width [mm]	Qty.	Order No.
ITA 1	25		1803800000
ITA 1/ZA	25		1803810000


Type	width [mm]	Qty.	Order No.
SWIFTY SET	1		9006060000
SD 0.6x3.5x100	1		9008330000

Type	width [mm]	Qty.	Order No.
IRH 1.5	100		1804510000


Type	width [mm]	Qty.	Order No.
WS 10/5			

Type	width [mm]	Qty.	Order No.
WS 10/5			

IPE 1.5N/4AN

1.5 mm²

5.1 x 93.5 x 40.5
/ 1.5
0.21 ... 1.5



IEC 60947-7-2 / IEC 60352-4

Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
1.5	AWG 24... 16	AWG 24... 16	1.5
500			
6			

3
/ V-0


KEMA 02ATEX2241 U

Rated connection	further connection
0.21...1.5	
0.21...1.5	


/ 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

IDK 1.5N/PE

1.5 mm²


5.1 x 100 x 54
/ 1.5
0.21 ... 1.5



IEC 60947-7-2 / IEC 60352-4

Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
1.5	AWG 24... 16	AWG 24... 16	1.5
500			
6			

3
/ V-0

KEMA 02ATEX2241 U

Rated connection	further connection
0.21...1.5	
0.21...1.5	


/ 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

IDK 1.5N DU-PE

1.5 mm²

5.1 x 100 x 54
17.5 / 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4; IEC 60947-7-2 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
1.5	AWG 24... 16	AWG 24... 16	1.5
500			
6			

3
/ V-0

KEMA 02ATEX2241 U

Rated connection	further connection
0.21...1.5	
0.21...1.5	

/ 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

Type	Qty.	Order No.
IPE 1.5N/4AN	100	1792620000

Type	Qty.	Order No.
IDK 1.5N PE	50	1792690000

Type	Qty.	Order No.
IDK 1.5N DU-PE	50	1881610000

Type	width [mm]	Qty.	Order No.
IAP 1.5N/4AN	2	50	1792470000

width [mm]	Qty.	Order No.
WEW-35/2	8	1061200000

ITA 1	25	1803800000
ITA 1/ZA	25	1803810000

SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

IRH 1.5	100	1804510000
---------	-----	------------

WS 10/5

Type	width [mm]	Qty.	Order No.
IAP 1.5N/DK	2	50	1792520000

width [mm]	Qty.	Order No.
WEW-35/2	8	1061200000

ITA 1	25	1803800000
ITA 1/ZA	25	1803810000

SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

IRH 1.5	100	1804510000
---------	-----	------------

WS 10/5

Type	width [mm]	Qty.	Order No.
IAP 1.5N/DK	2	50	1792520000

width [mm]	Qty.	Order No.
WEW-35/2	8	1061200000

ITA 1	25	1803800000
ITA 1/ZA	25	1803810000

SWIFTY	1	9006020000
SD 0.6x3.5x100	1	9008330000

IRH 1.5	100	1804510000
---------	-----	------------

WS 10/5

Modular PE terminals

When using ATEX certified components in hazardous area applications the installation instructions and the rated data for accessories in the technical appendix must be considered.

width x length x height with TS 35 x 7.5	mm
max. current / max. cond. cross-section	A/mm ²
max. clamping range	mm ²

Technical data

Rated data	
Rated cross-section	mm ²
Rated voltage to adjacent terminal	V
Rated impulse withstand voltage to adjacent terminal	kV
Short-time withstand current	A
Pollution severity	
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	

Clamped conductors (H05V/H07V)

Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Tightening torque range (clamping screw)	Nm
Tightening torque range (fixing screw)	Nm
Stripping length / Blade size	mm / -

2 clamped cables with same cross-section (H05V/H07V)

Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²

Note

Ordering data

Version	
	green/yellow Wemid

Note

Accessories

End plate	
	dark beige Wemid

End bracket	
	dark beige / beige

Testing / Checking

For testing wired terminal strips	Standard
	with spigot

Screwdrivers

with cutting device "swifty set"	
Standard	

Reducing sleeves

for conductors < 0.5 mm ² / < AWG 20	
for conductors < 1.0 mm ² / < AWG 18	


PEN jumper

Inserted into TN-S distributor between N and PE terminals

Marking systems	(see large assortment in catalogue 7)
	Marking tags

For detailed information on other accessories and applications see "Accessories"


IPE 2.5N

2.5 mm²

6.1 x 66.4 x 45.6

/ 2.5

0.5 ... 2.5

IEC 60947-7-2 / IEC 60352-4 Ex e II  II 2 G D

IEC	UL	CSA	EN 60079-7
-----	----	-----	------------

2.5	AWG 20... 14	AWG 20... 14	2.5
-----	--------------	--------------	-----

800			
-----	--	--	--

8			
---	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--


--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--


IPE 2.5N/3AN

2.5 mm²

6.1 x 87.9 x 45.6

/ 2.5

0.5 ... 2.5

IEC 60947-7-2 / IEC 60352-4 Ex e II  II 2 G D

IEC	UL	CSA	EN 60079-7
-----	----	-----	------------

2.5	AWG 20... 14	AWG 20... 14	2.5
-----	--------------	--------------	-----

800			
-----	--	--	--

8			
---	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--


--	--	--	--

--	--	--	--


--	--	--	--

IPE 2.5N/4AN

2.5 mm²



6.1 x 105.9 x 45.6
/ 2.5
0.5 ... 2.5



IEC 60947-7-2 / IEC 60352-4 Ex e II  II 2 G D

IEC	UL	CSA	EN 60079-7
2.5	AWG 20... 14	AWG 20... 14	2.5
800			
8			

3
/ V-0

 DEMKO 03ATEX134054U

Rated connection	further connection
0.5...2.5	
0.5...2.5	

/ 0.6 x 3.5

Type	Qty.	Order No.
IPE 2.5N/4AN	50	1812980000

Type	width [mm]	Qty.	Order No.
IAP 2.5N/4AN	2	50	1813070000

width [mm]			
WEW-35/2	8	100	1061200000

ITA 2	25	1821210000
ITA 2/ZA	25	1821220000

SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

IRH 2.5	100	1848230000
---------	-----	------------

WS 10/6

Double level terminals

Feed-through terminals

When using ATEX certified components in hazardous area applications the installation instructions and the rated data for accessories in the technical appendix must be considered.

width x length x height with TS 35 x 7.5 mm
 max. current / max. cond. cross-section A/mm²
 max. clamping range mm²

Technical data

Rated data	
Rated voltage	V
Rated current	A
Rated cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	kV/-
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Tightening torque range (clamping screw)	Nm
Stripping length / Blade size	mm / -

Note

Ordering data

Version	
	dark beige Wemid
	blue Wemid
Note	


Accessories

Cross-connection, pluggable	
	2-pole
	3-pole
	4-pole
	10-pole
	20-/24-pole
End plate / Partition plate	
	dark beige Wemid
	blue Wemid
End bracket	
	dark beige Wemid
Test adapter	
For testing wired terminal strips	Standard
	with spigot
Screwdrivers	
	with cutting device "swifty set"
	Standard
Reducing sleeves	
	for conductors < 0.5 mm / AWG 20
	for conductors < 1.0 mm / AWG 18
Cover	
	with lightning flash symbol
	blank
Labelling systems	
(see large assortment in catalogue 7)	Marking tags
For detailed information on other accessories and applications see "Accessories"	

IDK 1.5N

1.5 mm²

5.1 x 100 x 54
/ 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4 Ex e II  II 2 G D

IEC	UL	CSA	EN 60079-7
500	300	300	275
17.5	10	10	15
1.5	AWG 24... 16	AWG 24... 16	1.5
6 / 3			
/ V-0			




KEMA 02ATEX2241 U


Rated connection	further connection
0.21...1.5	
0.21...1.5	
/ 0.6 x 3.5	

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

IDK 1.5N/V

1.5 mm²

5.1 x 100 x 54
17.5 / 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4 Ex e II  II 2 G D

IEC	UL	CSA	EN 60079-7
500	300	300	275
17.5	10	10	15
1.5	AWG 24... 16	AWG 24... 16	1.5
6 / 3			
/ V-0			



KEMA 02ATEX2241 U

Rated connection	further connection
0.21...1.5	
0.21...1.5	
/ 0.6 x 3.5	

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

Type	Qty.	Order No.
IDK 1.5N	50	1792650000
IDK 1.5N BL	50	1792660000

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000

width [mm]		
IAP 1.5N/DK	2	50
IAP 1.5N/DK BL	2	50

width [mm]		
WEW-35/2	8	100

width [mm]		
ITA 1	25	1803800000
ITA 1/ZA	25	1803810000

width [mm]		
SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

width [mm]		
IRH 1.5	100	1804510000

width [mm]		
IAD 1/4 GE MIT BLITZ	20	1805500000
IAD 1/4 GE Neutral	20	1818420000

width [mm]		
WS 10/5		

Feed-through hybrid terminals

IDK 1.5N/ZB

1.5 mm²


When using ATEX certified components in hazardous area applications the installation instructions and the rated data for accessories in the technical appendix must be considered.

width x length x height with TS 35 x 7.5 mm
 max. current / max. cond. cross-section A/mm²
 max. clamping range mm²

5.1 x 95.5

/ 1.5

0.21 ... 1.5



Technical data

Rated data

Rated voltage V
 Rated current A
 Rated cross-section mm²
 Rated impulse withstand voltage / Pollution severity kV/-
 Gauge to IEC 60947-1 / UL94 Flammability class

Approvals

Clamped conductors (H05V/H07V)

Solid / stranded mm²
 Flexible / Flexible with wire end ferrule mm²
 Tightening torque range (clamping screw) Nm
 Stripping length / Blade size mm / -

IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
500	300	300	
17.5	10	10	
1.5	AWG 24... 16	AWG 24... 16	
		6 / 3	
		/ V-0	



Rated connection	further connection
0.21...1.5	0.5...4
0.21...1.5	0.5...4 / 0.5...2.5
	0.4...0.6 Nm / M 2.5
	10 / 0.6 x 3.5

Note

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

Ordering data

Version

dark beige Wemid
 blue Wemid

Note

Type	Qty.	Order No.
IDK 1.5N/ZB	50	1891950000
IDK 1.5N/ZB BL	50	1896720000

PE terminal IDK 1.5N/ZB PE: 1891970000; 4 connections at one potential with IDK 1.5N/ZB V: 1891960000

Accessories

Cross-connection, pluggable



2-pole
 3-pole
 4-pole
 10-pole
 20-/24-pole

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000

End plate / Partition plate

dark beige Wemid
 blue Wemid

width [mm]		
IAP 1.5N/DK-ZB	2	50
IAP 1.5N/DK-ZB BL	2	50

End bracket

dark beige Wemid

width [mm]		
WEW-35/2	8	100

Test adapter

For testing wired terminal strips

Standard
 with spigot

ITA 1	25	1803800000
ITA 1/ZA	25	1803810000

Screwdrivers

with cutting device "swifty set"
 Standard

SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

Reducing sleeves

for conductors < 0.5 mm / AWG 20
 for conductors < 1.0 mm / AWG 18

IRH 1.5	100	1804510000

Cover



with lightning flash symbol
 blank

IAD 1/4 GE MIT BLITZ	20	1805500000

Labelling systems (see large assortment in catalogue 7)

Marking tags

For detailed information on other accessories and applications see "Accessories"

Modular disconnect terminals

When using ATEX certified components in hazardous area applications the installation instructions and the rated data for accessories in the technical appendix must be considered.

width x length x height with TS 35 x 7.5	mm
max. current / max. cond. cross-section	A/mm ²
max. clamping range	mm ²

Technical data

Rated data	
Rated voltage, feed-through terminal	V
Rated current	A
Rated cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	kV/-
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Tightening torque range (clamping screw)	Nm
Stripping length / Blade size	mm / -
2 clamped cables with same cross-section (H05V/H07V)	
Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Note	


Ordering data

Version	
	dark beige Wemid
	blue Wemid
	without disconnecter, dark beige Wemid
Note	

Accessories

Cross-connection, pluggable	
	2-pole
	3-pole
	4-pole
	10-pole
End plate / Partition plate	
End plate	dark beige Wemid
Partition plate	dark beige Wemid
End bracket	
	dark beige
Screwdrivers	
	Standard
Test plug	
	Plug dia. 2.3 mm
Holder for cartridge fuse, 5 x 20mm	
	400 V ac/dc, without LED
	10-36 V ac/dc, red LED
	140-250V ac/dc, red LED
Module connector (max. 250 V)	
reversed insertion possible	without fittings
	with wire jumper
	with 1N4007 diode
Disconnecting plug	
	yellow Wemid
Labelling systems	
	(see large assortment in catalogue 7)
	Marking tags
For detailed information on other accessories and applications see "Accessories"	


ITR 1.5N

1.5 mm²

5.1 x 78.8 x 46.5

16 / 1.5

0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4 / VDE 0100-537

IEC	UL	CSA	EN 60079-7
400	300	300	
16	10	10	
1.5	AWG 24... 16	AWG 24... 16	
		6 / 3	
		/ V-0	



Rated connection

0.21...1.5

0.21...1.5

/ 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

Type	Qty.	Order No.
ITR 1.5N	100	1792630000
ITR 1.5N BL	100	1792670000
ITR 1.5N O.TNHE	100	1814160000

ITR 1.5N/3AN

1.5 mm²

5.1 x 93.5 x 46.5

/ 1.5

0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4 / VDE 0100-537

IEC	UL	CSA	EN 60079-7
400	300	300	
16	10	10	
1.5	AWG 24... 16	AWG 24... 16	
		6 / 3	
		/ V-0	



Rated connection

0.21...1.5

0.21...1.5

/ 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

Type	Qty.	Order No.
ITR 1.5N/3AN	100	1812510000
ITR 1.5N/3AN BL	100	1812520000

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000

width [mm]			
IAP 1.5N/3AN	2	50	1792450000

width [mm]			
IAP 1.5N/4AN	2	50	1792470000

width [mm]			
WEW-35/2	8	100	1061200000

width [mm]			
SD 0.6x3.5x100		1	9008330000

width [mm]			
SIHA 3/G20	25		7921560000

width [mm]			
SIHA 3/G20/LD 10-36V	25		7921560000

width [mm]			
SIHA 3/G20/LD 140-250V	25		7921560000

width [mm]			
BEST	50		1833100000

width [mm]			
BEST/DRBR	50		1878570000


width [mm]			
BEST/D	50		1878560000

width [mm]			
TNST	50		1833090000


To cross-connect to other IDC2 terminals use QVAR1 (see Accessories)

ITR 2.5N

2.5 mm²



6.1 x 87.9 x 49.5
/ 2.5
0.5 ... 2.5



IEC 60947-7-1 / IEC 60352-4 / VDE 0100-537

IEC	UL	CSA	EN 60079-7
400	300	300	
18	10	10	
2.5	AWG 20... 14	AWG 20... 14	
6 / 3			
/ V-0			



Rated connection

0.5...2.5

0.5...2.5

/ 0.6 x 3.5

Type	Qty.	Order No.
ITR 2.5N	100	1812990000
ITR 2.5N BL	100	1813000000
ITR 2.5N O.TNHE	100	1820500000

Type	Current [A]	Qty.	Order No.
ZQV 4/2 GE	32	60	1608950000
ZQV 4/3 GE	32	60	1608960000
ZQV 4/4 GE	32	60	1608970000
ZQV 4/10 GE	32	20	1609030000
width [mm]			
IAP 2.5N/3AN	2	50	1813040000
width [mm]			
WEW-35/2	8	100	1061200000
SD 0.6x3.5x100		1	9008330000
SIHA 3/G20		25	7921560000
SIHA 3/G20/LD 10-36V		25	7921560000
SIHA 3/G20/LD 140-250V		25	7921560000
BEST		50	1833100000
BEST/DRBR		50	1878570000
BEST/D		50	1878560000

WS 10/6

When using ATEX certified components in hazardous area applications the installation instructions and the rated data for accessories in the technical appendix must be considered.

width x length x height with TS 35 x 7.5 mm
max. current / max. cond. cross-section A/mm²
max. clamping range mm²

Technical data

Rated data	
Rated voltage, adjacent terminal	V
Rated current	A
Rated cross-section	mm²
Rated impulse withstand voltage / Pollution severity	kV /
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / stranded	mm²
Flexible / Flexible with wire end ferrule	mm²
Tightening torque range (clamping screw)	Nm
Stripping length / Blade size	mm / -
2 clamped cables with same cross-section (H05V/H07V)	
Solid / stranded	mm²
Flexible / Flexible with wire end ferrule	mm²
Note	

Ordering data

Version	
dark beige Wernid	400 V ac/dc, without LED 10-36 V ac/dc, with LED 30-70V ac/dc, with LED 60-150 V ac/dc, with LED 140-250V ac/dc, with LED

Note


Accessories

Cross-connection, pluggable		2-pole
		3-pole
		4-pole
		10-pole
End plate / Partition plate (after last terminal)		End plate, Wemid
		Partition plate, Wemid
Screwdrivers		Standard
Cartridge fuse, 5 x 20mm (IEC 60127-2)		
Rated voltage 250 V		0.25 A quick-blow
Rated breaking capacity 1500 A		0.5 A quick-blow
(at 250V / 50Hz / $\cos \varphi = 0.7$)		1 A quick-blow
		2 A quick-blow
G25 with indicator / imperial fuse		
G25 (DIN 41 576 / 250V)		0.5 A medium time-lag / 2 A
Rated voltage 250 V		1 A medium time-lag / 3 A
Imperial fuse, 1/4 x 1 1/4		2 A quick-blow / 5 A
Rated voltage 440 V		4 A quick-blow / 10 A
Labelling systems (see large assortment in catalogue 7)		Marking tags
For detailed information on other accessories and applications see "Accessories"		

ITR 1.5N/SI

1.5 mm²

5.1 x 78.5 x 88.5
17.5 / 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4 / VDE 0100-537

IEC	UL	CSA	EN 60079-7
250	300	300	
6.3	6.3	6.3	
1.5	AWG 24... 16	AWG 24... 16	
6 / 3			
/ V-0			
			
Rated connection			
0.21...1.5			
0.21...1.5			
/ 0.6 x 3.5			
Conductor < 0.5 mm² / AWG 24 with IRH 1.5; max. power loss (1.6 W) at cartridge fuse limits rated current of terminal.			

Type

Type	Qty.	Order No.
ITR 1.5N SI	25	1792640000

Type

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24 A	60	1608860000
ZQV 2.5/3	24 A	60	1608870000
ZQV 2.5/4	24 A	60	1608880000
ZQV 2.5/10	24 A	20	1608940000
	width [mm]		
IAP 1.5N/3AN	2	50	1792450000
SD 0.6x3.5x100		1	9008330000
SWIFTY SET		1	9006060000
G 20/0.25A/F		10	0430500000
G 20/0.5A/F		10	0430600000
G 20/1A/F		10	0430700000
G 20/2A/F		10	0430900000
WS 10/5			

ITR 1.5N/3AN/SI

1.5 mm²
$$\frac{5.1 \times 93.5 \times 88.8}{1.5}$$


IEC 60947-7-1 / IEC 60352-4 / VDE 0100-537

IEC	UL	CSA	EN 60079-7
250	300	300	
6.3	6.3	6.3	
1.5	AWG 24... 16	AWG 24... 16	
6 / 3			
/ V-0			
			
Rated connection			
0.21...1.5			
0.21...1.5			
/ 0.6 x 3.5			
Conductor < 0.5 mm² / AWG 24 with IPRH 1.5; max. power loss (1.6 W) at cartridge fuse limits rated current of terminal.			

Type

Type	Qty.	Order No.
ITR 1.5N/3AN SI	25	1820390000

Type


[illegible]

ITR 2.5N/SI

2.5 mm²



6.1 x 87.9 x 92.5
/ 2.5
0.21 ... 2.5



IEC 60947-7-1 / IEC 60352-4 / VDE 0100-537

IEC	UL	CSA	EN 60079-7
250	300	300	
6.3	6.3	6.3	
2.5	AWG 20... 14	AWG 20... 14	
/ 3			
/ V-0			



Rated connection

0.5...2.5
0.5...2.5

/ 0.6 x 3.5

Type	Qty.	Order No.
ITR 2.5N SI	25	1813010000

Max. power loss (1.6 W) at the cartridge fuse limits the rated current.

Type	Current [A]	Qty.	Order No.
ZQV 4/2 GE	32 A	60	1608950000
ZQV 4/3 GE	32 A	60	1608960000
ZQV 4/4 GE	32 A	60	1608970000
ZQV 4/10 GE	32 A	20	1609030000
width [mm]			
IAP 2.5N	2	50	1813020000
SD 0.6x3.5x100		1	9008330000
SWIFTY SET		1	9006060000
G 20/0.25A/F		10	0430500000
G 20/0.5A/F		10	0430600000
G 20/1A/F		10	0430700000
G 20/2A/F		10	0430900000

WS 10/6

Hybrid modular terminals

Feed-through terminals

IDU 1.5N/ZF

1.5 mm²

IDU 1.5N/ZF/3AN

1.5 mm²

When using ATEX certified components in hazardous area applications the installation instructions and the rated data for accessories in the technical appendix must be considered.

width x length x height with TS 35 x 7.5 mm
 max. current / max. cond. cross-section A/mm²
 max. clamping range mm²

Technical data

Rated data	
Rated voltage	V
Rated current	A
Rated cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	kV/-
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Tightening torque range (clamping screw)	Nm
Stripping length / Blade size	mm / -


Note

Ordering data


Version	
	dark beige Wemid
	blue Wemid
Note	

Accessories

Cross-connection, pluggable	
	2-pole
	3-pole
	4-pole
	10-pole
	20-/24-pole
End plate / Partition plate	
	dark beige Wemid
	blue Wemid
End bracket	
	dark beige Wemid
Test adapter	
For testing wired terminal strips	Standard
	with spigot
Screwdrivers	
	with cutting device "swifty set"
	Standard
Reducing sleeves	
	for conductors < 0.5 mm / AWG 20
	for conductors < 1.0 mm / AWG 18
Cover	
	with lightning flash symbol
	blank
Labelling systems	
(see large assortment in catalogue 7)	Marking tags
For detailed information on other accessories and applications see "Accessories"	

5.1 x 59.5 x 40.5			
/ 1.5			
0.21 ... 1.5			
			
IEC 60947-7-1 / IEC 60352-4			
Ex e II  II 2 G D			
IEC	UL	CSA	EN 60079-7
500	300	300	275
17.5	10	10	15
1.5	AWG 24... 16	AWG 24... 16	1.5
6 / 3			
/ V-0			
			
KEMA 02ATEX2241 U			
Rated connection		further connection	
0.21...1.5		0.5...4	
0.21...1.5		0.5...4 / 0.5...2.5	
/ 0.6 x 3.5		10 / 0.6 x 3.5	

Conductor < 0.5 mm² / AWG 24 with IRH 1.5
 32 A continuous current for cross-connection (for supply)

5.1 x 78.5 x 40.5			
/ 1.5			
0.21 ... 1.5			
			
IEC 60947-7-1 / IEC 60352-4			
Ex e II  II 2 G D			
IEC	UL	CSA	EN 60079-7
500	300	300	275
17.5	10	10	
1.5	AWG 24... 16	AWG 24... 16	1.5
6 / 3			
/ V-0			
			
KEMA 02ATEX2241 U			
Rated connection		further connection	
0.21...1.5		0.5...4	
0.21...1.5		0.5...4 / 0.5...2.5	
/ 0.6 x 3.5		10 / 0.6 x 3.5	

Conductor < 0.5 mm² / AWG 24 with IRH 1.5
 32 A continuous current for cross-connection (for supply)

Type	Qty.	Order No.
IDU 1.5N/ZF	100	1792700000
IDU 1.5N/ZF BL	100	1792710000

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000

Type	width [mm]	Qty.	Order No.
IAP 1.5N/3AN	2	50	1792450000
IAP 1.5N/3AN BL	2	50	1792460000

Type	width [mm]	Qty.	Order No.
WEW-35/2	8	100	1061200000

Type	Qty.	Order No.
ITA 1	25	1803800000
ITA 1/ZA	25	1803810000

Type	Qty.	Order No.
SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

Type	Qty.	Order No.
IRH 1.5	100	1804510000

Type	Qty.	Order No.
IAD 1/4 GE MIT BLITZ	20	1805500000
IAD 1/4 GE Neutral	20	1818420000

Type	Qty.	Order No.
WS 10/5		

IDU 1.5N/ZB

1.5 mm²

5.1 x 59.5 x 40.5
/ 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4 Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
500	300	300	275
17.5	10	10	15
1.5	AWG 24... 16	AWG 24... 16	1.5
6 / 3			
/ V-0			




KEMA 02ATEX2241 U


Rated connection	further connection
0.21...1.5	0.5...4
0.21...1.5	0.5...4 / 0.5...2.5
	0.4...0.6 Nm / M 2.5
/ 0.6 x 3.5	10 / 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5
32 A continuous current for cross-connection (for supply)

IDU 1.5N/ZB/3AN

1.5 mm²

5.1 x 78.5 x 40.5
/ 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4 Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
500	300	300	275
17.5	10	10	15
1.5	AWG 24... 16	AWG 24... 16	1.5
6 / 3			
/ V-0			




KEMA 02ATEX2241 U

Rated connection	further connection
0.21...1.5	0.5...4
0.21...1.5	0.5...4 / 0.5...2.5
	0.4...0.6 Nm / M 2.5
/ 0.6 x 3.5	10 / 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5
32 A continuous current for cross-connection (for supply)

IDU 2.5N/ZF

2.5 mm²

6.1 x 66.4 x 45.6
/ 2.5
0.5 ... 2.5



IEC 60947-7-1 / IEC 60352-4 Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
800	600	600	550
24	15	15	21
2.5	AWG 20... 14	AWG 20... 14	2.5
8 / 3			
/ V-0			



DEMKO 03ATEX134054U

Rated connection	further connection
0.5...2.5	0.5...6
0.5...2.5	0.5...6 / 0.5...4
/ 0.6 x 3.5	10 / 0.6 x 3.5

Type	Qty.	Order No.
IDU 1.5N/ZB	100	1792730000
IDU 1.5N/ZB BL	100	1792740000

Type	Qty.	Order No.
IDU 1.5N/3AN/ZB	100	1806170000
IDU 1.5N/3AN/ZB BL	100	1819480000

Type	Qty.	Order No.
IDU 2.5N/ZF	100	1821260000
IDU 2.5N/ZF BL	100	1821270000

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000

width [mm]			
IAP 1.5N	2	50	1792430000
IAP 1.5N BL	2	50	1792440000
width [mm]			
WEW-35/2	8	100	1061200000

ITA 1	25	1803800000
ITA 1/ZA	25	1803810000
SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

IRH 1.5	100	1804510000
---------	-----	------------

IAD 1/4 GE MIT BLITZ	20	1805500000
IAD 1/4 GE Neutral	20	1818420000

WS 10/5

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000

width [mm]			
IAP 1.5N/3AN	2	50	1792450000
IAP 1.5N/3AN BL	2	50	1792460000
width [mm]			
WEW-35/2	8	100	1061200000

ITA 1	25	1803800000
ITA 1/ZA	25	1803810000
SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

IRH 1.5	100	1804510000
---------	-----	------------

IAD 1/4 GE MIT BLITZ	20	1805500000
IAD 1/4 GE Neutral	20	1818420000

WS 10/5

Type	Current [A]	Qty.	Order No.
ZQV 4/2 GE	32	60	1608950000
ZQV 4/3 GE	32	60	1608960000
ZQV 4/4 GE	32	60	1608970000
ZQV 4/10 GE	32	20	1609030000
ZQV 4/20 GE	32	20	1909010000

width [mm]			
IAP 2.5N	2	50	1813020000
IAP 2.5N BL	2	50	1813030000
width [mm]			
WEW-35/2	8	100	1061200000

ITA 2	25	1821210000
ITA 2/ZA	25	1821220000
SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

IRH 2.5	100	1848230000
---------	-----	------------

IAD 2/4 GE MIT BLITZ	20	1828420000
IAD 2/4 GE NEUTRAL	20	1828430000

WS 10/6

Hybrid modular terminals

Feed-through terminals

IDU 2.5N/ZB

2.5 mm²

IDU 2.5N/3AN/ZB

2.5 mm²

When using ATEX certified components in hazardous area applications the installation instructions and the rated data for accessories in the technical appendix must be considered.

width x length x height with TS 35 x 7.5 mm
 max. current / max. cond. cross-section A/mm²
 max. clamping range mm²

Technical data

Rated data	
Rated voltage	V
Rated current	A
Rated cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	kV/-
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Tightening torque range (clamping screw)	Nm
Stripping length / Blade size	mm / -


Note

Ordering data

Version	
	dark beige Wemid
	blue Wemid
Note	

Accessories

Cross-connection, pluggable	
	2-pole
	3-pole
	4-pole
	10-pole
	20-/24-pole
End plate / Partition plate	
	dark beige Wemid
	blue Wemid
End bracket	
	dark beige Wemid
Test adapter	
For testing wired terminal strips	Standard
	with spigot
Screwdrivers	
	with cutting device "swifty set"
	Standard
Reducing sleeves	
	for conductors < 0.5 mm / AWG 20
	for conductors < 1.0 mm / AWG 18
Cover	
	with lightning flash symbol
	blank
Labelling systems	
(see large assortment in catalogue 7)	Marking tags
For detailed information on other accessories and applications see "Accessories"	



6.1 x 66.4 x 45.6

/ 2.5

0.5 ... 2.5

ZB

Y

Y

IDC

IEC 60947-7-1 / IEC 60352-4

Ex e II  II 2 G D

IEC	UL	CSA	EN 60079-7
800	600	600	550
24	15	15	21
2.5	AWG 20... 14	AWG 20... 14	2.5

8 / 3

/ V-0








DEMKO 03ATEX134054U

Rated connection	further connection
0.5...2.5	0.5...6
0.5...2.5	0.5...6 / 0.5...4
	0.5...0.8 Nm
/ 0.6 x 3.5	13 / 0.6 x 3.5

Note



6.1 x 87.9 x 45.6			
/ 2.5			
0.5 ... 2.5			
			
IEC 60947-7-1 / IEC 60352-4			
Ex e II  II 2 G D			
IEC	UL	CSA	EN 60079-7
800	600	600	550
24	15	15	21
2.5	AWG 20... 14	AWG 20... 14	2.5
8 / 3			
/ V-0			
			
DEMKO 03ATEX134054U			
Rated connection		further connection	
0.5...2.5		0.5...6	
0.5...2.5		0.5...6 / 0.5...4	
/ 0.6 x 3.5		0.5...0.8 Nm	
		13 / 0.6 x 3.5	

Note

1.5 mm²

5.1 x 78.5 x 40.5
/ 1.5
0.21 ... 1.5

The diagram shows a horizontal line representing a cable with two conductors. The left conductor is labeled 'ZF' and the right conductor is labeled 'IDC'. A ground symbol, consisting of three horizontal lines of decreasing width, is connected to the line between the two conductors and is labeled 'PE'.

IEC 60947-7-2 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
1.5	AWG 24... 16	AWG 24... 16	1.5
500			
6			
	3		
	/ V-0		
			KEMA 02ATEX2241 U
Rated connection		further connection	
0.21...1.5		0.5...4	
0.21...1.5		0.5...4 / 0.5...2.5	
/ 0.6 x 3.5		10 / 0.6 x 3.5	
Conductor < 0.5 mm² / AWG 24 with IIRH 1.5			

Type	Qty.	Order No.
IPE 1.5N/3AN/ZF	100	1806140000

Type	width [mm]	Qty.	Order No.
IAP 1.5N/3AN	2	50	1792450000
width [mm]			
WEW-35/2	8	100	1061200000
ITA 1		25	1803800000
ITA 1/ZA		25	1803810000
SWIFTY SET		1	9006060000
SD 0.6x3.5x100		1	9008330000
IRH 1.5		100	1804510000
WS 10/5			

Hybrid modular terminals

Modular PE terminals

IPE 1.5N/ZB

1.5 mm²

IPE 1.5N/ZB/3AN

1.5 mm²

When using ATEX certified components in hazardous area applications the installation instructions and the rated data for accessories in the technical appendix must be considered.

width x length x height with TS 35 x 7.5	mm
max. current / max. cond. cross-section	A/mm ²
max. clamping range	mm ²

Technical data

Rated data	
Rated cross-section	mm ²
Rated voltage to adjacent terminal	V
Rated impulse withstand voltage to adjacent terminal	kV
Short-time withstand current	A
Pollution severity	
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	

Clamped conductors (H05V/H07V)

Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Tightening torque range (clamping screw)	Nm
Tightening torque range (fixing screw)	Nm
Stripping length / Blade size	mm / -

2 clamped cables with same cross-section (H05V/H07V)

Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²

Note

Ordering data

Version	
	green/yellow Wemid

Note

Accessories

End plate	
	dark beige Wemid

End bracket	
	dark beige / beige

Testing / Checking

For testing wired terminal strips	Standard
	with spigot

Screwdrivers

with cutting device "swifty set"	
Standard	

Reducing sleeves


for conductors < 0.5 mm ² / < AWG 20	
for conductors < 1.0 mm ² / < AWG 18	

PEN jumper

Inserted into TN-S distributor between N and PE terminals

Marking systems	(see large assortment in catalogue 7)
	Marking tags

For detailed information on other accessories and applications see "Accessories"



5.1 x 59.5 x 40.5	
/ 1.5	
0.21 ... 1.5	

IEC 60947-7-2 / IEC 60352-4 Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
1.5	AWG 24... 16	AWG 24... 16	1.5
500			
6			
	3		
	/ V-0		

KEMA 02ATEX2241 U

Rated connection	further connection
0.21...1.5	0.5...4
0.21...1.5	0.5...4 / 0.5...2.5
	0.4...0.6 Nm
/ 0.6 x 3.5	10 / 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5



5.1 x 78.5 x 40.5	
/ 1.5	
0.21 ... 1.5	

IEC 60947-7-2 / IEC 60352-4 Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
1.5	AWG 24... 16	AWG 24... 16	1.5
500			
6			
	3		
	/ V-0		

KEMA 02ATEX2241 U

Rated connection	further connection
0.21...1.5	0.5...4
0.21...1.5	0.5...4 / 0.5...2.5
	0.4...0.6 Nm
/ 0.6 x 3.5	10 / 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

Type	Qty.	Order No.
IPE 1.5N/ZB	100	1792750000

Note

Type	width [mm]	Qty.	Order No.
IPE 1.5N/3AN	2	50	1792450000

	width [mm]		
WEW-35/2	8	100	1061200000

ITA 1	25	1803800000
ITA 1/ZA	25	1803810000

SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000


IRH 1.5	100	1804510000
---------	-----	------------

Note


Marking systems	(see large assortment in catalogue 7)
	Marking tags

WS 10/5

IPE 2.5N/ZF

2.5 mm²

6.1 x 66.4 x 45.6
/ 2.5
0.5 ... 2.5



IEC 60947-7-2 / IEC 60352-4

Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
2.5	AWG 20... 14	AWG 20... 14	2.5
800			
8			

3	
/ V-0	




DEMKO 03ATEX134054U


Rated connection	further connection
0.5...2.5	0.5...6
0.5...2.5	0.5...6 / 0.5...4

/ 0.6 x 3.5	10 / 0.6 x 3.5
-------------	----------------

IPE 2.5N/ZB

2.5 mm²

6.1 x 66.4 x 45.6
/ 2.5
0.5 ... 2.5



IEC 60947-7-2 / IEC 60352-4

Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
2.5	AWG 20... 14	AWG 20... 14	2.5
800			
8			

3	
/ V-0	




DEMKO 03ATEX134054U


Rated connection	further connection
0.5...2.5	0.5...6
0.5...2.5	0.5...6 / 0.5...4
	0.5...0.8 Nm / M 3

/ 0.6 x 3.5	13 / 0.6 x 3.5
-------------	----------------

IPE 2.5N/3AN/ZB

2.5 mm²

6.1 x 87.9 x 45.6
/ 2.5
0.5 ... 2.5



IEC 60947-7-2 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
2.5	AWG 20... 14	AWG 20... 14	
800			
8			

3	
/ V-0	



Rated connection	further connection
0.5...2.5	0.5...6
0.5...2.5	0.5...6 / 0.5...4
	0.5...0.8 Nm

/ 0.6 x 3.5	13 / 0.6 x 3.5
-------------	----------------

Type	Qty.	Order No.
IPE 2.5N/ZF	100	1821280000

Type	Qty.	Order No.
IPE 2.5N/ZB	100	1821310000

Type	Qty.	Order No.
IPE 2.5N/3AN/ZB	100	1848320000

Type	width [mm]	Qty.	Order No.
IAP 2.5N	2	50	1813020000

width [mm]	Qty.	Order No.
WEW-35/2	8	1061200000

ITA 2	25	1821210000
ITA 2/ZA	25	1821220000

SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

IRH 2.5	100	1848230000
---------	-----	------------

WS 10/6		
---------	--	--

Type	width [mm]	Qty.	Order No.
IAP 2.5N	2	50	1813020000

width [mm]	Qty.	Order No.
WEW-35/2	8	1061200000

ITA 2	25	1821210000
ITA 2/ZA	25	1821220000

SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

IRH 2.5	100	1848230000
---------	-----	------------

WS 10/6		
---------	--	--

Type	width [mm]	Qty.	Order No.
IAP 2.5N/3AN	2	50	1813040000

width [mm]	Qty.	Order No.
WEW-35/2	8	1061200000

ITA 2	25	1821210000
ITA 2/ZA	25	1821220000

SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000


IRH 2.5	100	1848230000
---------	-----	------------

WS 10/6		
---------	--	--

Hybrid modular terminals

Double level terminals

IDK 1.5N/ZB

1.5 mm²


When using ATEX certified components in hazardous area applications the installation instructions and the rated data for accessories in the technical appendix must be considered.

width x length x height with TS 35 x 7.5 mm
 max. current / max. cond. cross-section A/mm²
 max. clamping range mm²

5.1 x 95.5

/ 1.5

0.21 ... 1.5



Technical data

Rated data	
Rated voltage	V
Rated current	A
Rated cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	kV/-
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Tightening torque range (clamping screw)	Nm
Stripping length / Blade size	mm / -

IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
500	300	300	
17.5	10	10	
1.5	AWG 24... 16	AWG 24... 16	
		6 / 3	
		/ V-0	



Rated connection	further connection
0.21...1.5	0.5...4
0.21...1.5	0.5...4 / 0.5...2.5
	0.4...0.6 Nm / M 2.5
	10 / 0.6 x 3.5

Note

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

Ordering data

Version
dark beige Wemid
blue Wemid

Note

Type	Qty.	Order No.
IDK 1.5N/ZB	50	1891950000
IDK 1.5N/ZB BL	50	1896720000

PE terminal IDK 1.5N/ZB PE: 1891970000; 4 connections at one potential with IDK 1.5N/ZB V: 1891960000

Accessories

Cross-connection, pluggable	
	2-pole
	3-pole
	4-pole
	10-pole
	20-/24-pole

End plate / Partition plate	
	dark beige Wemid
	blue Wemid

End bracket	
	dark beige Wemid

Test adapter	
For testing wired terminal strips	Standard
	with spigot

Screwdrivers	
	with cutting device "swifty set"
	Standard

Reducing sleeves	
	for conductors < 0.5 mm / AWG 20
	for conductors < 1.0 mm / AWG 18

Cover	
	with lightning flash symbol
	blank

Labelling systems	
(see large assortment in catalogue 7)	Marking tags

For detailed information on other accessories and applications see "Accessories"

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000

width [mm]			
IAP 1.5N/DK-ZB	2	50	1896710000
IAP 1.5N/DK-ZB BL	2	50	1896730000

width [mm]			
WEW-35/2	8	100	1061200000

ITA 1	25		1803800000
ITA 1/ZA	25		1803810000

SWIFTY SET	1		9006060000
SD 0.6x3.5x100	1		9008330000

IRH 1.5	100		1804510000

IAD 1/4 GE MIT BLITZ	20		1805500000

Pluggable standard terminal featuring IDC technology

Profit from the amazing benefits of IDC2 technology

quick – secure – compact


in combination with a pluggable standard terminal.

The basic principle is beautifully simple:

One terminal strip for the function unit, one plug-in connector for cable harness assembly. During final assembly, the two units just have to be slotted into each other – like plug-in connectors. And that's all there is to it!


You'll soon be convinced by the benefits of this technology:

Quick assembly of functional units which can be fully tested in the factory, quickly and easily replaced or reassemble on site.



Plug-in cross-connections

- 2 to 10 pole or “continuous” for individual assembly
- Full rated current
- Break-off pole for bypassing other potentials
- Plug-in connectors are also designed for use of cross-connections



Contact reliability

- Maintenance-free connection
- Gas-tight contact area
- 100% vibration-resistant

Push-on connection

The tensioned steel contact ensures galvanic isolation.

- High contact strength with highly conductive properties

You can find a large selection of plug-in connectors in the “Accessories” chapter.




Secure fixing

All plug-in units can be locked securely to the terminal strip by means of separate locking elements.




IT 1.5N/4AN/2

1.5 mm²

5.1 x 93.5 x 40.7

/ 1.5

0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
500	300	300	
690			
17.5	10	10	
1.5	AWG 24... 16	AWG 24... 16	
6 / 3			
/ V-0			



Rated connection	pluggable connection
0.21...1.5	0.5...4
0.21...1.5	0.5...4 / 0.5...2.5
/ 0.6 x 3.5	

Conductor < 0.5 mm² / AWG 24 with IIRH 1.5


ITPE 1.5N/4AN/2

1.5 mm²

5.1 x 93.5 x 41.5

/ 1.5

0.21 ... 1.5



IEC 60947-7-2 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
500	300	300	
690			
17.5	10	10	
1.5	AWG 24... 16	AWG 24... 16	
6 / 3			
/ V-0			



Rated connection	pluggable connection
0.21...1.5	0.5...4
0.21...1.5	0.5...4 / 0.5...2.5
/ 0.6 x 3.5	

Conductor < 0.5 mm² / AWG 24 with IIRH 1.5

When using ATEX certified components in hazardous area applications the installation instructions and the rated data for accessories in the technical appendix must be considered.

width x length x height with TS 35 x 7.5 mm
max. current / max. cond. cross-section A/mm²
max. clamping range mm²

Technical data

Rated data	
Rated voltage	V
max. voltage of clamp support & pluggable system	V
Rated current	A
Rated cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	kV/-
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Stripping length / Blade size	mm / -
Note	

Ordering data

Base terminal	
	dark beige Wemid
pluggable connector	
	For detailed information on all variations see "Accessories"
1-pole	
2-pole	
3-pole	
4-pole	
5-pole	
6-pole	
8-pole	
10-pole	
Note	

Type	Qty.	Order No.
IT 1.5N/4AN/2	50	1837250000
ZP 2.5/1AN/QV/1	50	1815190000
ZP 2.5/1AN/QV/2	25	1815200000
ZP 2.5/1AN/QV/3	25	1815210000
ZP 2.5/1AN/QV/4	25	1815220000
ZP 2.5/1AN/QV/5	25	1815230000
ZP 2.5/1AN/QV/6	25	1815240000
ZP 2.5/1AN/QV/8	20	1815260000
ZP 2.5/1AN/QV/10	20	1815280000

Type	Qty.	Order No.
ITPE 1.5N/4AN/2	50	1837260000
ZP 2.5/1AN/QV/1	50	1815190000
ZP 2.5/1AN/QV/2	25	1815200000
ZP 2.5/1AN/QV/3	25	1815210000
ZP 2.5/1AN/QV/4	25	1815220000
ZP 2.5/1AN/QV/5	25	1815230000
ZP 2.5/1AN/QV/6	25	1815240000
ZP 2.5/1AN/QV/8	20	1815260000
ZP 2.5/1AN/QV/10	20	1815280000

Accessories

Cross-connection, pluggable	
	
2-pole	
3-pole	
4-pole	
10-pole	
20-pole	
End plate	
dark beige Wemid	
orange Wemid	
Test adapter	
Standard	
with spigot	
Miscellaneous accessories, WeiCoS	
Locking element	
Coding element	
Strain relief	
Screwdrivers	
with cutting device "swifty set"	
Standard	
Labelling systems	
(see large assortment in catalogue 7)	
Marking tags	
For detailed information on other accessories and applications see "Accessories"	

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000
width [mm]			
IAP/TW IT1.5N/4AN	2	50	1837270000
width [mm]			
ITA 1		25	1803800000
ITA 1/ZA		25	1803810000
ZVR ZP2.5		25	1816130000
KOSF ZT2.5		50	1816150000
ZZE ZP2.5		25	1816140000
SWIFTY SET		1	9006060000
SD 0.6x3.5x100		1	9008330000
width [mm]			
WS 10/5			

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000
width [mm]			
IAP/TW IT1.5N/4AN	2	50	1837270000
width [mm]			
ITA 1		25	1803800000
ITA 1/ZA		25	1803810000
ZVR ZP2.5		25	1816130000
KOSF ZT2.5		50	1816150000
ZZE ZP2.5		25	1816140000
SWIFTY SET		1	9006060000
SD 0.6x3.5x100		1	9008330000
width [mm]			
WS 10/5			

The modular initiator/actuator system with integrated cross-connection – featuring advanced IDC technology

The principle

Two current bars in the individual terminal (or three with separate PE / earth function) are used to provide potentials. They are supplied via a supply terminal and the internal crossconnections. Two other current bars act as a feed-through terminal for forwarding signals.

The internal cross-connection


The cross-connections are already integrated within the individual terminals. The female contact is on one side of the terminal and the male contact on the other. The modular design means that variable terminal strips can be created for different applications.

The end plate

End plates enable additional marking of the rows.

The status indication


The signal status can be indicated directly at the terminal.



The alternative versions


• Supply terminal

Supply made easy with additional options for marking.




• Initiator terminal

Power supply and signal transmission in one terminal; available in a 3- or 4-conductor version.




• Actuator terminal

Simple connection of actuators.



• Initiator terminal with parking position

For connecting 4L initiators:
The NCC/NOC currently not in use can be connected to the insulated contact, so that rewiring later on is no problem.



When using ATEX certified components in hazardous area applications the installation instructions and the rated data for accessories in the technical appendix must be considered.

width x length x height with TS 35 x 7.5	mm
max. current / max. conductor	A/mm ²
max. clamping range	mm ²

Technical data

Rated data	
Rated voltage	V
Rated current	A
Rated cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	kV/-
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	
Electronic fittings	
Diode reverse voltage / Diode current	V / A
voltage LED / current LED / polarity	V / mA / -
Resistor / Varistor	-/V
Clamped conductors (H05V/H07V)	
Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Tightening torque range (clamping screw)	Nm
Stripping length / Blade size	mm / -
Note	


Ordering data

Version	
Terminal configuration	dark beige Wemid
see circuit diagram above	dark beige Wemid (red LED)
Note	

Accessories

Cross-connection, pluggable	
	2-pole
	3-pole
	4-pole
	10-pole
	20-/24-pole
End plate / Partition plate	
	dark beige Wemid
End bracket	
	dark beige / beige
Screwdrivers	
	with cutting device "swifty set"
	Standard
Reducing sleeves	
	for conductors < 0.5 mm ² / < AWG 20
	for conductors < 1.0 mm ² / < AWG 18
Labelling systems	
	(see large assortment in catalogue 7)
	Marking tags
For detailed information on other accessories and applications see "Accessories"	

IEK 1.5N 3L

1.5 mm²

5.1 x 93 x 51	
/ 1.5	0 0
0.21 ... 1.5	


IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
250	300	300	
17.5	10	10	
1.5	AWG 24... 16	AWG 24... 16	
		4 / 3	
		/ V-0	



Rated connection	further connection
0.21...1.5	
0.21...1.5	
	/ 0.6 x 3.5
Conductor < 0.5 mm ² / AWG 24 with IRH 1.5	

IEK 1.5N 3L PE

1.5 mm²

5.1 x 93 x 51	
/ 1.5	0 PE 0
0.21 ... 1.5	

IEC 60947-7-2 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
250	300	300	
17.5	10	10	
1.5	AWG 24... 16	AWG 24... 16	
		4 / 3	
		/ V-0	



Rated connection	further connection
0.21...1.5	
0.21...1.5	
	/ 0.6 x 3.5
Conductor < 0.5 mm ² / AWG 24 with IRH 1.5	

Type	Qty.	Order No.
IEK 1.5N 3L	25	1801790000
IEK 1.5N 3L PE	25	1801800000

Type	Qty.	Order No.
IEK 1.5N 3L	25	1801790000

Type	Current [A]	Qty.	Order No.
IAP 1.5N 3L	2	20	1801770000
WEW-35/2	8	100	1061200000
SWIFTY SET		1	9006060000
SD 0.6x3.5x100		1	9008330000
IRH 1.5		100	1804510000
WS 10/5			

Type	Current [A]	Qty.	Order No.
IAP 1.5N 3L	2	20	1801770000
WEW-35/2	8	100	1061200000
SWIFTY SET		1	9006060000
SD 0.6x3.5x100		1	9008330000
IRH 1.5		100	1804510000
WS 10/5			

Initiator and actuator terminals

When using ATEX certified components in hazardous area applications the installation instructions and the rated data for accessories in the technical appendix must be considered.

width x length x height with TS 35 x 7.5	mm
max. current / max. conductor	A/mm ²
max. clamping range	mm ²

Technical data

Rated data	
Rated voltage	V
Rated current	A
Rated cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	kV/-
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	
Electronic fittings	
Diode reverse voltage / Diode current	V / A
voltage LED / current LED / polarity	V / mA / -
Resistor / Varistor	-/V
Clamped conductors (H05V/H07V)	
Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Tightening torque range (clamping screw)	Nm
Stripping length / Blade size	mm / -
Note	


Ordering data

Version	
Terminal configuration	dark beige Wemid
see circuit diagram above	dark beige Wemid (red LED)
Note	

Accessories

Cross-connection, pluggable	
	2-pole
	3-pole
	4-pole
	10-pole
	20-/24-pole
End plate / Partition plate	
	dark beige Wemid
End bracket	
	dark beige / beige
Screwdrivers	
	with cutting device "swifty set"
	Standard
Reducing sleeves	
	for conductors < 0.5 mm ² / < AWG 20
	for conductors < 1.0 mm ² / < AWG 18
Labelling systems	
	(see large assortment in catalogue 7)
	Marking tags
For detailed information on other accessories and applications see "Accessories"	

IEK 1.5N 4L PE

1.5 mm²

5.1 x 112 x 51			
/ 1.5	+	-	PE
0.21 ... 1.5			


IEC 60947-7-2 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
250	300	300	
17.5	10	10	
1.5	AWG 24... 16	AWG 24... 16	
		4 / 3	
		/ V-0	



Rated connection	further connection
0.21...1.5	
0.21...1.5	
	/ 0.6 x 3.5
Conductor < 0.5 mm ² / AWG 24 with IRH 1.5	

IAK 1.5N 3L

1.5 mm²

5.1 x 93 x 51			
/ 1.5	-	PE	
0.21 ... 1.5			

IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
250	300	300	
17.5	10	10	
1.5	AWG 24... 16	AWG 24... 16	
		4 / 3	
		/ V-0	




Rated connection	further connection
0.21...1.5	
0.21...1.5	
	/ 0.6 x 3.5
Conductor < 0.5 mm ² / AWG 24 with IRH 1.5	


Type	Qty.	Order No.
IAK 1.5N 3L	50	1801820000
Base terminal with LED: IAK 1.5N 3L D: 1801830000		

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000
width [mm]			
IAP 1.5N 3L	2	20	1801770000
width [mm]			
WEW-35/2	8	100	1061200000
SWIFTY SET	1		9006060000
SD 0.6x3.5x100	1		9008330000
IRH 1.5	100		1804510000
width [mm]			
WS 10/5			

IIK 1.5N 3L

1.5 mm²

5.1 x 93 x 51
/ 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
250	300	300	
17.5	10	10	
1.5	AWG 24... 16	AWG 24... 16	
	4 / 3		
	/ V-0		



Rated connection **further connection**


0.21...1.5

0.21...1.5


/ 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

IIK 1.5N 4L

1.5 mm²

5.1 x 112 x 51
/ 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
250	300	300	
17.5	10	10	
1.5	AWG 24... 16	AWG 24... 16	
	4 / 3		
	/ V-0		



Rated connection **further connection**


0.21...1.5

0.21...1.5


/ 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

IIK 1.5N 4L PA

1.5 mm²

5.1 x 112 x 51
/ 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
250	300	300	
17.5	10	10	
1.5	AWG 24... 16	AWG 24... 16	
	4 / 3		
	/ V-0		



Rated connection **further connection**

0.21...1.5

0.21...1.5

/ 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

Type	Qty.	Order No.
IIK 1.5N 3L	50	1801840000

Base terminal with LED: IIK 1.5N 3L D/PNP 1801850000, IIK 1.5N 3L D/NPN 1801860000

Type	Qty.	Order No.
IIK 1.5N 4L	50	1801870000

Base terminal with LED: IIK 1.5N 4L D/PNP 1801880000, IIK 1.5N 4L D/NPN 1801890000

Type	Qty.	Order No.
IIK 1.5N 4L PA	50	1801900000

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000
width [mm]			
IAP 1.5N 3L	2	20	1801770000
width [mm]			
WEW-35/2	8	100	1061200000
width [mm]			
SWIFTY SET	1		9006060000
SD 0.6x3.5x100	1		9008330000
width [mm]			
IRH 1.5		100	1804510000

WS 10/5

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000
width [mm]			
IAP 1.5N 4L	2	20	1801780000
width [mm]			
WEW-35/2	8	100	1061200000
width [mm]			
SWIFTY SET	1		9006060000
SD 0.6x3.5x100	1		9008330000
width [mm]			
IRH 1.5		100	1804510000

WS 10/5

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000
width [mm]			
IAP 1.5N 4L	2	20	1801780000
width [mm]			
WEW-35/2	8	100	1061200000
width [mm]			
SWIFTY SET	1		9006060000
SD 0.6x3.5x100	1		9008330000
width [mm]			
IRH 1.5		100	1804510000

WS 10/5

Initiator and actuator terminals

When using ATEX certified components in hazardous area applications the installation instructions and the rated data for accessories in the technical appendix must be considered.

width x length x height with TS 35 x 7.5	mm
max. current / max. conductor	A/mm ²
max. clamping range	mm ²

Technical data

Rated data	
Rated voltage	V
Rated current	A
Rated cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	kV/-
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	
Electronic fittings	
Diode reverse voltage / Diode current	V / A
voltage LED / current LED / polarity	V / mA / -
Resistor / Varistor	-/V
Clamped conductors (H05V/H07V)	
Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Tightening torque range (clamping screw)	Nm
Stripping length / Blade size	mm / -
Note	


Ordering data

Version	
Terminal configuration	dark beige Wemid
see circuit diagram above	dark beige Wemid (red LED)
Note	


Accessories

Cross-connection, pluggable	
	2-pole
	3-pole
	4-pole
	10-pole
	20-/24-pole
End plate / Partition plate	
	dark beige Wemid
End bracket	
	dark beige / beige
Screwdrivers	
	with cutting device "swifty set"
	Standard
Reducing sleeves	
	for conductors < 0.5 mm ² / < AWG 20
	for conductors < 1.0 mm ² / < AWG 18
Labelling systems	
	(see large assortment in catalogue 7)
	Marking tags
For detailed information on other accessories and applications see "Accessories"	

IAK 1.5N 3L D

1.5 mm²


5.1 x 93 x 51
/ 1.5
0.21 ... 1.5




IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
250	300	300	
17.5	10	10	
1.5	AWG 24... 16	AWG 24... 16	
		4 / 3	
		/ V-0	
Rated connection further connection			
0.21...1.5			
0.21...1.5			
/ 0.6 x 3.5			
Conductor < 0.5 mm ² / AWG 24 with IRH 1.5			

IIK 1.5N 3L D/PNP

1.5 mm²

5.1 x 93 x 51
/ 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4



IEC	UL	CSA	EN 60079-7
250	300	300	
17.5	10	10	
1.5	AWG 24... 16	AWG 24... 16	
		4 / 3	
		/ V-0	
Rated connection further connection			
0.21...1.5			
0.21...1.5			
/ 0.6 x 3.5			
Conductor < 0.5 mm ² / AWG 24 with IRH 1.5			

Type	Qty.	Order No.
IAK 1.5N 3L D	50	1801830000
IIE 1.5N 3L D		
IIF 1.5N 3L D		
IIG 1.5N 3L D		
IIL 1.5N 3L D		
IIM 1.5N 3L D		
IIN 1.5N 3L D		
IIO 1.5N 3L D		
IIP 1.5N 3L D		
IIS 1.5N 3L D		
IIT 1.5N 3L D		
IIV 1.5N 3L D		
IIX 1.5N 3L D		
IIZ 1.5N 3L D		

Type	Current [A]	Qty.	Order No.
IAP 1.5N 3L	2	20	1801770000
WEW-35/2	8	100	1061200000
SWIFTY SET		1	9006060000
SD 0.6x3.5x100		1	9008330000
IRH 1.5		100	1804510000
WS 10/5			

IIK 1.5N 3L D/NPN

1.5 mm²


$$\frac{5.1 \times 93 \times 51}{1.5} = 0.21 \dots 1.5$$


IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
250	300	300	
17.5	10	10	
1.5	AWG 24... 16	AWG 24... 16	
	4 / 3		
	/ V-0		

Rated connection	further connection
0.21...1.5	
0.21...1.5	

/ 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

Type	Qty.	Order No.
IIK 1.5N 3L D/NPN	50	1801860000

Type	Current [A]	Qty.	Order No.
	width [mm]		
IAP 1.5N 3L	2	20	1801770000
	width [mm]		
WEW-35/2	8	100	1061200000
SWIFTY SET		1	9006060000
SD 0.6x3.5x100		1	9008330000
IRH 1.5		100	1804510000


WS 10/5

IIK 1.5N 4L D/PNP

1.5 mm²


$$\frac{5.1 \times 112 \times 51}{1.5}$$

0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
250	300	300	
17.5	10	10	
1.5	AWG 24... 16 AWG 24... 16		
4 / 3			
/ V-0			

Rated connection	further connection
0.21...1.5	
0.21...1.5	

/ 0.6 x 3.5

Conductor $< 0.5 \text{ mm}^2$ / AWG 24 with IRH 1.5


Type	Qty.	Order No.
IIK 1.5N 4L D/PNP	50	1801880000

Type	Current [A]	Qty.	Order No.
	width [mm]		
IAP 1.5N 4L	2	20	1801780000
	width [mm]		
WEW-35/2	8	100	1061200000
SWIFTY SET		1	9006060000
SD 0.6x3.5x100		1	9008330000
IRH 1.5		100	1804510000

WS 10/5

IIK 1.5N 4L D/NPN

1.5 mm²


$$\frac{5.1 \times 112 \times 51}{1.5}$$


IEC 60947-7-1 / IEC 60352-4

IEC 60364-7-710 EN 60364-7	UL	CSA	EN 60079-7
250	300	300	
17.5	10	10	
1.5	AWG 24... 16	AWG 24... 16	
	4 / 3		
	/ V-0		

Rated connection	further connection
0.21...1.5	
0.21...1.5	

/ 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

Type	Qty.	Order No.
IIK 1.5N 4L D/NPN	50	1801890000

Type	Current [A]	Qty.	Order No.
	width [mm]		
IAP 1.5N 4L	2	20	1801780000
	width [mm]		
WEW-35/2	8	100	1061200000
SWIFTY SET		1	9006060000
SD 0.6x3.5x100		1	9008330000
IRH 1.5		100	1804510000

WS 10/5

Terminals with electronic components

When using ATEX certified components in hazardous area applications the installation instructions and the rated data for accessories in the technical appendix must be considered.

width x length x height with TS 35 x 7.5	mm
max. current / max. conductor	A/mm ²
max. clamping range	mm ²

Technical data

Rated data	
Rated voltage	V
Rated current	A
Rated cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	kV/-
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	
Electronic fittings	
Diode reverse voltage / Diode current	V / A
voltage LED / current LED / polarity	V / mA / -
Resistor / Varistor	-/V
Clamped conductors (H05V/H07V)	
Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Tightening torque range (clamping screw)	Nm
Stripping length / Blade size	mm / -
Note	

Ordering data

Version	
Terminal configuration	dark beige Wemid
see circuit diagram above	dark beige Wemid (red LED)
Note	


Accessories

Cross-connection, pluggable	
	2-pole
	3-pole
	4-pole
	10-pole
	20-/24-pole
End plate / Partition plate	
	dark beige Wemid
End bracket	
	dark beige / beige
Screwdrivers	
	with cutting device "swifty set"
	Standard
Reducing sleeves	
	for conductors < 0.5 mm ² / < AWG 20
	for conductors < 1.0 mm ² / < AWG 18
Labelling systems	
	(see large assortment in catalogue 7)
	Marking tags
For detailed information on other accessories and applications see "Accessories"	

IDK 1.5N/D1

1.5 mm²

5.1 x 100 x 54
/ 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
500	300	300	
10	10	15	
1.5	AWG 24... 16	AWG 24... 16	
		6 / 3	
		/ V-0	




Rated connection	further connection
0.21...1.5	
0.21...1.5	
	/ 0.6 x 3.5
Soldered diode: Type 1N 4007, reverse voltage 1000 V, current 1 A; current of continuous busbar = 10 A	

IDK 1.5N/D2

1.5 mm²

5.1 x 100 x 54
/ 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
500	300	300	
10	10	15	
1.5	AWG 24... 16	AWG 24... 16	
		6 / 3	
		/ V-0	




Rated connection	further connection
0.21...1.5	
0.21...1.5	
	/ 0.6 x 3.5
Soldered diode: Type 1N 4007, reverse voltage 1000 V, current 1 A; current of continuous busbar = 10 A	

IDK 1.5N/D4

1.5 mm²

5.1 x 100 x 54
/ 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
500			
10			
1.5	AWG 24... 16	AWG 24... 16	
	6 / 3		
	/ V-0		

Rated connection **further connection**


0.21...1.5

0.21...1.5


/ 0.6 x 3.5

Soldered diode: Type 1N 4007, reverse voltage 1000 V, current 1 A; current of continuous busbar = 10 A

IDK 1.5N/D5

1.5 mm²

5.1 x 100 x 54
/ 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
500			
10			
1.5	AWG 24... 16	AWG 24... 16	
	6 / 3		
	/ V-0		

Rated connection **further connection**


0.21...1.5

0.21...1.5


/ 0.6 x 3.5

Soldered diode: Type 1N 4007, reverse voltage 1000 V, current 1 A; current of continuous busbar = 10 A

IDK 1.5N/D6

1.5 mm²

5.1 x 100 x 54
/ 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
500			
10			
1.5	AWG 24... 16	AWG 24... 16	
	6 / 3		
	/ V-0		

Rated connection **further connection**

0.21...1.5

0.21...1.5

/ 0.6 x 3.5

Soldered diode: Type 1N 4007, reverse voltage 1000 V, current 1 A; current of continuous busbar = 10 A

Type	Qty.	Order No.
IDK 1.5N/D4	50	1820050000

Type	Qty.	Order No.
IDK 1.5N/D5	50	1820060000

Type	Qty.	Order No.
IDK 1.5N/D6	50	1820070000

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000
width [mm]			
IAP 1.5N/DK	2	50	1792520000
width [mm]			
WEW-35/2	8	100	1061200000
SWIFTY SET	1		9006060000
SD 0.6x3.5x100	1		9008330000
IRH 1.5		100	1804510000

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000
width [mm]			
IAP 1.5N/DK	2	50	1792520000
width [mm]			
WEW-35/2	8	100	1061200000
SWIFTY SET	1		9006060000
SD 0.6x3.5x100	1		9008330000
IRH 1.5		100	1804510000

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000
width [mm]			
IAP 1.5N/DK	2	50	1792520000
width [mm]			
WEW-35/2	8	100	1061200000
SWIFTY SET	1		9006060000
SD 0.6x3.5x100	1		9008330000
IRH 1.5		100	1804510000

WS 10/5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

WS 10/5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

WS 10/5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5

Terminals with electronic components

When using ATEX certified components in hazardous area applications the installation instructions and the rated data for accessories in the technical appendix must be considered.

width x length x height with TS 35 x 7.5	mm
max. current / max. conductor	A/mm ²
max. clamping range	mm ²

Technical data

Rated data	
Rated voltage	V
Rated current	A
Rated cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	kV/-
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	
Electronic fittings	
Diode reverse voltage / Diode current	V / A
voltage LED / current LED / polarity	V / mA / -
Resistor / Varistor	-/V
Clamped conductors (H05V/H07V)	
Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Tightening torque range (clamping screw)	Nm
Stripping length / Blade size	mm / -
Note	


Ordering data

Version	
Terminal configuration	dark beige Wemid
see circuit diagram above	dark beige Wemid (red LED)
Note	


Accessories

Cross-connection, pluggable	
	2-pole
	3-pole
	4-pole
	10-pole
	20-/24-pole
End plate / Partition plate	
	dark beige Wemid
End bracket	
	dark beige / beige
Screwdrivers	
	with cutting device "swifty set"
	Standard
Reducing sleeves	
	for conductors < 0.5 mm ² / < AWG 20
	for conductors < 1.0 mm ² / < AWG 18
Labelling systems	
	(see large assortment in catalogue 7)
	Marking tags
For detailed information on other accessories and applications see "Accessories"	

IDK 1.5N/DX1

1.5 mm²


5.1 x 100 x 54
/ 1.5
0.21 ... 1.5




IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
500			
10			
1.5	AWG 24... 16	AWG 24... 16	
		6 / 3	
		/ V-0	
Rated connection			
0.21...1.5			
0.21...1.5			
/ 0.6 x 3.5			
Note			
Soldered diode: Type 1N 4007, reverse voltage 1000 V, current 1 A; current of continuous busbar = 10 A			

IDK 1.5N/LD

1.5 mm²

5.1 x 100 x 54
/ 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
500			
10			
1.5	AWG 24... 16	AWG 24... 16	
		6 / 3	
		/ V-0	
Rated connection			
0.21...1.5			
0.21...1.5			
/ 0.6 x 3.5			
Note			
Conductor < 0.5 mm ² / AWG 24 with IRH 1.5 Current of LED < 5mA			

Type	Qty.	Order No.
IDK 1.5N/LD 150V	50	1820720000
Note		
IDK 1.5N/LD 36V: 1820090000 IDK 1.5N/LD 250V: 1820730000		


Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000
width [mm]			
IAP 1.5N/DK	2	50	1792520000
width [mm]			
WEW-35/2	8	100	1061200000
width [mm]			
SWIFTY SET	1		9006060000
SD 0.6x3.5x100	1		9008330000
width [mm]			
IRH 1.5	100		1804510000
width [mm]			
WS 10/5			
Conductor < 0.5 mm ² / AWG 24 with IRH 1.5			

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000
width [mm]			
IAP 1.5N/DK	2	50	1792520000
width [mm]			
WEW-35/2	8	100	1061200000
width [mm]			
SWIFTY SET	1		9006060000
SD 0.6x3.5x100	1		9008330000
width [mm]			
IRH 1.5	100		1804510000
width [mm]			
WS 10/5			

IDK 1.5N/S07 K140

1.5 mm²

5.1 x 100 x 54
/ 1.5
0.21 ... 1.5



IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
115	115	115	
10	10	10	
1.5	AWG 24... 16	AWG 24... 16	
	6 / 3		
	/ V-0		



Rated connection **further connection**

0.21...1.5
0.21...1.5


/ 0.6 x 3.5

Conductor < 0.5 mm² / AWG 24 with IRH 1.5
Varistor type: S07 K140

IDU 2.5N/2X2AN/D+

2.5 mm²

6.1 x 105.9 x 45.6
/ 2.5
0.5 ... 2.5



IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
500	300	300	
10			
2.5	AWG 20... 14	AWG 20... 14	
	6 / 3		
	/ V-0		



Rated connection **further connection**

0.5...2.5
0.5...2.5


/ 0.6 x 3.5

Soldered diode: Type 1N 4007, reverse voltage 1000 V, current 1 A

IDU 2.5N/2X2AN/D-

2.5 mm²

6.1 x 105.6 x 45.6
/ 2.5
0.5 ... 2.5



IEC 60947-7-1 / IEC 60352-4

IEC	UL	CSA	EN 60079-7
500	300	300	
10			
2.5	AWG 20... 14	AWG 20... 14	
	6 / 3		
	/ V-0		



Rated connection **further connection**

0.5...2.5
0.5...2.5

/ 0.6 x 3.5

Soldered diode: Type 1N 4007, reverse voltage 1000 V, current 1 A

Type	Qty.	Order No.
IDK 1.5N/U S07 K140	50	1820110000

Type	Qty.	Order No.
IDU 2.5N/2X2AN/D+	50	1821240000

Type	Qty.	Order No.
IDU 2.5N/2X2AN/D-	50	1821250000

Type	Current [A]	Qty.	Order No.
ZQV 2.5/2	24	60	1608860000
ZQV 2.5/3	24	60	1608870000
ZQV 2.5/4	24	60	1608880000
ZQV 2.5/10	24	20	1608940000
ZQV 2.5/20	24	20	1908960000

width [mm]			
IAP 1.5N/DK	2	50	1792520000

width [mm]			
WEW-35/2	8	100	1061200000

SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

IRH 1.5	100	1804510000
---------	-----	------------

WS 10/5

Type	Current [A]	Qty.	Order No.
IAP 2.5N/4AN	2	50	1813070000
WEW-35/2	8	100	1061200000

width [mm]			
IAP 2.5N/4AN	2	50	1813070000

width [mm]			
WEW-35/2	8	100	1061200000

SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

IRH 2.5	100	1848230000
---------	-----	------------

WS 10/6

Type	Current [A]	Qty.	Order No.
IAP 2.5N/4AN	2	50	1813070000
WEW-35/2	8	100	1061200000

width [mm]			
IAP 2.5N/4AN	2	50	1813070000

width [mm]			
WEW-35/2	8	100	1061200000

SWIFTY SET	1	9006060000
SD 0.6x3.5x100	1	9008330000

IRH 2.5	100	1848230000
---------	-----	------------


WS 10/6

Additional functions

Weidmüller offers users a full range of accessories for I-Series terminals, providing optimum solutions to every conceivable task – even outside the range of standard functions. All Weidmüller accessories are built to the same quality standards as the terminals themselves.

Visual separation

Page C.44



End plates and partition plates have the function of guaranteeing “finger-touch safety” in terminal strips by preventing finger contact with any conducting parts. In addition, end plates and partition plates are also used for visual separation of circuits.

This visual separation can be enhanced by using coloured end plates.


Labelling and connecting

Chapter F



Weidmüller labelling systems featured in **chapter F** are used to mark IDC terminals.

Weidmüller IDC2 terminals are connected using a standard 0.6 x 3.5 screwdriver. Here our **Swifty®** screwdriver with combined cutting function (see **page F.65**) is a very clever solution.



Fastening

Chapter F



An end bracket is fitted on the mounting rail to the right and left of the terminals to ensure that they sit firmly in position. The marking surface of the end bracket can also be used for group marking. The wide range of Weidmüller end brackets and mounting rails can be found in **Chapter F**.

Electrical supply

Page C.45



Weidmüller IDC2 terminals come with the **ZE1 16** supply terminal. Cross-connections break the current input down into several current outputs. The current is supplied with a conductor cross-section of 16 mm² and then distributed across neighbouring terminals for cross-sectional areas of 1.5 mm² and 2.5 mm².

Electrical distribution

Page C.46




A plug-in **cross-connection system (ZQV)** is supplied for all Weidmüller terminals.

Potential is distributed to any number of terminals simply by plugging the cross-section into the middle of the terminals.

Pluggable terminals ...

Page C.30


**... with IDC technology**

In its design, the terminals are based on the modular principle. The basic elements of the WeiCoS system consist of one terminal assembly for the functional unit on the mounting rail, and plug-in connectors connecting up the elements (cable harness assembly).

- Quick assembly
- Fully plugged-in functional units possible
- Quick and simple replacement during servicing

Testing


Page C.48



The latching test adapter (**ITA**) is used as a single unit and as a test adapter strip for measurements in control cabinets. The test adapter allows convenient, rational testing of assembled terminals. It is simply latched onto the terminal. This creates contact with the current carrying busbar. The unit is released from the terminal by simply pressing the release button.

Specific functions

Page C.50




For the IDC terminals there are also further accessories available, e.g.

- Pluggable fuse holder (SIHA 3)
- Reducing bush for centring small conductors

Accessories – Visual separation

End plates/partition plates



End plates are fastened to the open side of the final terminal before the end bracket. The use of end plates maintains both the function of the terminal and the required rated voltage.

The end terminal is safe from finger touch, protecting against shocks from conducting parts.


If cross-connections are shortened, end plates must be used on the bare cut edges of the cross-connection to maintain the rated voltage of 250 V.

Coloured end plates are used to enhance the visual separation between different electric circuits.


Ordering data

Type	Colour	Qty	Order No.	For terminal type
IAP 1.5N	beige	50	1792430000	IDU 1.5N
IAP 1.5N BL	blue	50	1792440000	IDU 1.5N/ZF IDU 1.5N /ZB
IAP 1.5N/3AN	beige	50	1792450000	IDU 1.5N/3AN
IAP 1.5N/3AN BL	blue	50	1792460000	IDU 1.5N/3AN/ZF IDU 1.5N/3AN/ZB ITR 1.5N ITR 1.5N/SI
IAP 1.5N/4AN	beige	50	1792470000	IDU 1.5N/4AN
IAP 1.5N/4AN BL	blue	50	1792480000	ITR 1.5/3AN ITR 1.5/3AN/SI
IAP 1.5N/DK-ZB	beige	50	1896710000	IDK 1.5N/ZB
	blue	50	1896730000	
IAP 1.5N/DK	beige	50	1792520000	IDK 1.5N
IAP 1.5N/DK BL	blue	50	1792530000	IDK 1.5N/V IDK 1.5N/DU-PE
IAP 1.5N 3L	beige	20	1801770000	IAK 1.5N 3L IHK 1.5N 3L
IAP 1.5N 4L	beige	20	1801780000	IHK 1.5N 4L IHK 1.5N 4L PA
IAP 2.5N	beige	50	1813020000	IDU 2.5
IAP 2.5N BL	blue	50	1813030000	IDU 2.5N/ZB IDU 2.5N/ZF
IAP 2.5N/3AN	beige	50	1813040000	IDU 2.5N/3AN
IAP 2.5N/3AN BL	blue	50	1813050000	ITR 2.5N ITR 2.5N/SI
IAP 2.5N/4AN	beige	50	1813070000	IDU 2.5N/4AN
IAP 2.5N/4AN BL	blue	50	1813080000	


ZEI 16 supply terminal



The **ZEI 16** supply terminal is capable of taking conductor cross-sectional areas of up to 25 mm². Standard cross-connections then distribute the current to any number of terminals with a smaller cross-sectional area.



Cross-connection to ITR 1.5N/3AN with QVAR 1 (cross-connection adapter)



Power supply with the IEPL feed plate

Supply options and corresponding cross-connections

Output terminals Supply terminals		right									
		IDU 1.5N	IDU 1.5N/3AN	IDU 1.5N/4AN	IDU 2.5N	IDU 2.5N/3AN	IDU 2.5N/4AN		ITR 1.5N	ITR 1.5N/3AN	ITR 2.5N
left											
ZDU 4		x ¹	x	x	x ¹	x	x		x	x ²	x
ZDU 4 / 3 AN		x ¹	x ¹	x ¹	x ¹	x ¹	x ¹		x ¹	x ²	x ¹
ZDU 4 / 4 AN		x ¹	x ¹	x ¹	x ¹	x ¹	x		x ¹	x ²	x ¹
ZDU 6		x ¹	x	x	x	x	x		x	x ²	x
ZDU 6 / 3 AN		x ¹	x ¹	x ¹	x ¹	x ¹	x ¹		x ¹	x ²	x ¹
ZEI 16		x	x	x	x	x	x		x	x ²	x
left											
Output terminals Supply terminals		IDU 1.5N	IDU 1.5N/3AN	IDU 1.5N/4AN	IDU 2.5N	IDU 2.5N/3AN	IDU 2.5N/4AN		ITR 1.5N	ITR 1.5N/3AN	ITR 2.5N
		right									
ZDU 4		x ¹	x ¹	x ¹	x ¹	x ¹	x ¹		x ¹	x ²	x ¹
ZDU 4 / 3 AN		x	x ¹	x ¹	x	x ¹	x ¹		x ¹	x ²	x ¹
ZDU 4 / 4 AN		x	x	x	x	x	x ¹		x	x ²	x
ZDU 6		x	x ¹	x ¹	x	x ¹	x ¹		x ¹	x ²	x ¹
ZDU 6 / 3 AN		x	x ¹	x ¹	x	x ¹	x ¹		x ¹	x ²	x ¹
ZEI 16		x	x ¹	x ¹	x	x ¹	x ¹		x ¹	x ²	x ¹

x¹ with IEPL, x² with QVAR


Ordering data

Type	Colour	Qty	Order No.
ZEI 16	dark beige	20	1745350000
ZEI 16 BL	blue	20	1766240000
IEPL	dark beige	20	1859570000
QVAR1	dark beige	20	1836370000

Maximum possible current I_{max}

Output terminals	Cross-connection	Supply conductor cross-sectional area	Supply left or right	Supply middle
IDU 1.5N	ZQV 2.5	25 mm ²	62 A	95 A
IDU 2.5N	ZQV 4	25 mm ²	82 A	101 A

Plug-in cross-connection ZQV



The time-saving, easy-to-use cross-connection combs for terminals, featuring tension clamp technology.

- **ZQV 2.5** as 2- to 10-pole combs and ZQV2.5/20 – continuous (20-pole)
- **ZQV 4** as 2- to 10-pole combs and ZQV4/20 – continuous (20-pole)

These versions come with complete shock protection. However, please note that the rated voltage is reduced to 400 V when using cross-connections.

This does not apply to terminals with a rated voltage below 500 V. Here the rated voltage of the used terminal is mandatory (e.g. terminal types ITR 1.5N and ITR 2.5N).

Breaking out contact elements

Breaking out one or more (max. 60%) contact elements from cross-connections enables certain terminals to be bypassed to suit the application.

Fitting and changing cross-connection

The fitting and changing of cross-connections is a trouble-free and fast operation:

- Insert the cross-connection into the cross-conn. channel in the terminal...

...and press it fully home.

(The cross-connection may not project from the channel.)

- Remove a cross-connection by simply prising it out with a screwdriver.

Shortening cross-connections



Cross-connections can be shortened in length using a suitable cutting tool, e.g. KT ZQV (order no. 900217). However, three contact elements must always be retained.

Caution:

Contact elements must not be deformed!



If a cross-connection is shortened, end plates or partition plates (ZAP/TW) must be used to maintain the rated voltage of 250 V (fitted to the bare cut edges of the cross-connection).



Tailor-made cross-connections

ZQV 2.5/50 is a cross-connection which can be used for connecting up to 20 individual terminals easily and quickly. The fitter simply cuts off the required number of poles from the 20-pole cross-connection comb. With this system, cross-connections with the correct number of poles are always available and only a minimum of storage space is required.

The large number of poles in the 20-pole comb means that unused residual quantities are virtually avoided. The ends of the continuous cross-connection are bare.

In the interests of stability, 2-pole cross-connections are not permitted. An end plate must always be fitted to neighbouring ZQVs with bare cut edges. With the ZDU 2.5 and WDU 2.5N it is sufficient to fit the ZQV in the offset position. The rated voltage is 400 V.

ZQV 2.5



Type	Qty	Order No.
ZQV 2.5/2	60	1608860000
ZQV 2.5/3	60	1608870000
ZQV 2.5/4	60	1608880000
ZQV 2.5/5	20	1608890000
ZQV 2.5/6	20	1608900000
ZQV 2.5/7	20	1608910000
ZQV 2.5/8	20	1608920000
ZQV 2.5/9	20	1608930000
ZQV 2.5/10	20	1608940000
ZQV 2.5/20	10	1908960000
For terminal type		
IDU 1.5N...		
IDK 1.5N...		
ITR 1.5N...		
ITR 1.5N/SI...		
IT 1.5N/4 AN/2		
IAK 1.5N 3L		
IIK 1.5N 3L		
IIK 1.5N 4L		
IIK 1.5N 4L PA		

ZQV 4



Type	Qty	Order No.
ZQV 4/2	60	1608950000
ZQV 4/3	60	1608960000
ZQV 4/4	60	1608970000
ZQV 4/5	20	1608980000
ZQV 4/6	20	1608990000
ZQV 4/7	20	1609000000
ZQV 4/8	20	1609010000
ZQV 4/9	20	1609020000
ZQV 4/10	20	1609030000
ZQV 4/20	20	1909010000
For terminal type		
IDU 2.5N...		
ITR 2.5N...		
ITR 2.5N/SI...		

IRH


Reducing sleeves

Reducing sleeves are used to make it easier to connect conductors with smaller cross-sectional areas. The reducing sleeve centres the conductor in the middle of the IDC2 contact.

Type	Qty	Order No.
IRH 1.5 for terminals IDU 1.5	100	1804510000
IRH 2.5 for terminals IDU 2.5N	100	1848230000

Accessories – Testing

Test adapter



The ITA slot-in test adapter is used as both a single unit and a test adapter strip for measurements in switchgear cabinets.

Conductors with cross-sectional areas ranging from 0.5 mm² to 1.0 mm² can be clamped. The test adapter is simply slotted into the terminal, creating secure contact with the current carrying busbar. This connection is released again by simply pressing the release button.

Test plug



There is a test point for the PS 2.3 test plug in some terminals of the I-Series. For quick measurements, simply insert the test plug into the opening provided.

This is different from the test adapter in that the test plug does not slot into the terminal.

ITA 1



Dimensions	
Height	mm
Length	mm
Modular width	mm
Stripping length	mm
Rated voltage / current / cross-section	
IEC 60 947-7-1	
Clamping conductor	
Solid	mm ²
Flexible	mm ²
Torque	Nm
Ordering data	
1-pole	
with clip-in pivot	

Height	mm	76
Length	mm	27
Modular width	mm	5.1
Stripping length	mm	6.0
Rated voltage / current / cross-section		
500 V / 12 A / 1.0 mm ²		
Clamping conductor		
Solid	mm ²	0.5 ... 1.0
Flexible	mm ²	0.5 ... 1.0
Torque	Nm	0.4
Ordering data		
Type	Qty	Order No.
ITA 1	25	1803800000
ITA 1 / ZA	25	1803810000
For terminal type		
IDU 1.5N...		
IDK 1.5N...		
ITR 1.5N...		
ITR 1.5N/SI...		
IT 1.5N/4 AN/2		

ITA 2



Height	mm	76
Length	mm	27
Modular width	mm	6.1
Stripping length	mm	6.0
Rated voltage / current / cross-section		
500 V / 12 A / 1.0 mm ²		
Clamping conductor		
Solid	mm ²	0.5 ... 1.0
Flexible	mm ²	0.5 ... 1.0
Torque	Nm	0.4
Ordering data		
Type	Qty	Order No.
ITA 2	25	1821210000
ITA 2 / ZA	25	1821220000
For terminal type		
IDU 2.5N...		
ITR 2.5N...		
ITR 2.5N/SI		

PS 2.3

Plug diameter 2.3 mm



Type	Qty	Order No.
PS 2.3 RD	20	0180400000
For terminal type		
ITR 1.5N		
ITR 1.5N/3 AN		
ITR 2.5N		

Marking / Covering



The VDE regulations stipulate that mains connection terminals have to be covered.

For this purpose Weidmüller provides yellow covers printed with a warning arrow.

The covers slot into the screwdriver opening of the terminal, and are available in 4-pole terminal units.

IAD 1/4



Type	Qty	Order No.
IAD 1/4	20	1805500000
IAD 1/4 blank	20	1818420000

For terminal type	
IDU 1.5N...	IT 1.5N/4 AN/2
IDK 1.5N...	IAK 1.5N 3L
ITR 1.5N...	IIK 1.5N 3L
ITR 1.5N/SI...	IIK 1.5N 4L
	IIK 1.5N 4L PA

IAD 2/4



Type	Qty	Order No.
IAD 2/4	20	1828420000
IAD 2/4 blank	20	1828430000

For terminal type	
IDU 2.5N...	
ITR 2.5N...	
ITR 2.5N/SI...	


Snap Mark



Technical data	
Material	Polyamide
Flammability class to UL94	V-2
Temperature range	-40°C...100°C
Colour	white

Type	Length / Width [mm]	Qty	Order No.
Snap Mark I	23.0	50	1805880000

SIHA fuse holder



For 5 x 20 G-fuse cartridges

The SIHA fuse holder converts a simple terminal into a fuse terminal in next to no time. Simply remove the disconnect lever and insert the fuse plug.

- Simple handling without tools
- Housing made of Wemid (V0)
- Rated current 6.3 A
- 1.6 W power loss to DIN VDE 0611-6 at 23°C ambient temperature (also for 1.5 times rated current – composite arrangement)

- Even fits on 5 mm wide terminals when fitted in offset arrangement
- Marking position for Dekafix 5 and space for the E-Fix self-adhesive label, size 8/20



1. Open fuse holder with fingers or screw-driver



2. Press out old fuse



3. Position new fuse



4. Press fuse holder together again

SIHA 3



	Qty	Order No.
without LED		
SIHA3/G20		
400 V	1	7921560000
with LED (red)		
SIHA3/G20		
10 - 36 V	1	7921570000
35 - 70 V	1	7921580000
60 - 150 V	1	7921590000
140 - 250 V	1	7921600000
For terminal type		
ITR 1.5 N		
ITR 1.5 N / 3 AN		
ITR 2.5 N		

SIHA STRAP



	Qty	Order No.
with strap		
SIHA STRAP		
	20	9537680000
Connector for retro-fit assembly		
• Receptacle in the terminal is the marking position		
• Integrated marking position on the strap		
• Slots into fuse holder either on the left or on the right		

Cartridge fuses and gauge pieces for Weidmüller fuse terminals and SIHA 3 fuse holder

Cartridge fuses

For terminal type	Technical data / Ordering data					
ITR 1.5N/SI ITR 1.5N/3AN/SI ITR 2.5N/SI	G-type cartridge fuses 5 x 20 without indicators to IEC 60127-2 (VDE 0820 pt 2)					
	Size (mm)	Nom. voltage (V)	Nom. current (A)	Type	Qty	Order No.
	5 x 20		0.1	(F) G 20/0.10A/F	10	0430300000
	breaking capacity 1500 A (at 250 V, 50 Hz, cos φ 0.7)		0.2	(F) G 20/0.20A/F	10	0430400000
			0.25	(F) G 20/0.25A/F	10	0430500000
			0.5	(F) G 20/0.50A/F	10	0430600000
			0.63	(F) G 20/0.63A/F	10	0439000000
		250	1.0	(F) G 20/1.00A/F	10	0430700000
			1.6	(F) G 20/1.60A/F	10	0430800000
			2.0	(F) G 20/2.00A/F	10	0430900000
			2.5	(F) G 20/2.50A/F	10	0431000000
			3.15	(F) G 20/3.15A/F	10	0431100000
			4.0	(F) G 20/4.00A/F	10	0431200000
			5.0	(F) G 20/5.00A/F	10	0431300000
			6.3	(F) G 20/6.30A/F	10	0431400000
			(M) = medium-blow (F) = fast-blow			

Component/isolating plugs

The Weidmüller philosophy is to realise a multitude of applications with just a few parts. The component and isolating plugs (BEST and TNST) represent a logical extension of this cost-effective and efficient approach. The component plug can accommodate electronic components and connect them to the terminal. And once an isolating plug is removed, the clamping point is obviously disconnected. The opening is easy to recognise.

An unintentional reconnection of the circuit is prevented by simply removing the isolating plug. The BEST and the TNST have the same pin arrangement. Both plugs are also identical with the SIHA 3 fuse holder, meaning that they can be used in all the "disconnecting products" of the W-, Z-, I- and P-Series.

Component plug (up to 250 V)

can be reversed



Ordering data

Type	Fitted with...	Qty	Order No.
BEST	-	25	1833100000
BEST/ DRBR	wire jumper	25	1878570000
BEST/D	diode 1N4007	25	1878560000

For terminal type

ITR 1.5 w/o TNHE lever
ITR 2.5 w/o TNHE lever

Isolating plug

Isolating plug



Ordering data

Type	Colour	Qty	Order No.
TNST	yellow Wemid	25	1833090000

For terminal type

ITR 1.5 w/o TNHE lever
ITR 2.5 w/o TNHE lever

