

3TG10 Power Relays/Miniature Contactors

4-pole, 4 kW

Overview

Version

The 3TG10 power relays/miniature contactors with 4 main contacts are available with screw terminals or 6.3 mm × 0.8 mm flat connectors. The versions with screw terminals are climate-proof and finger-safe according to EN 61140.

The 3TG10 power relays/miniature contactors are small. Their width is 36 mm.

Application

Because they are hum-free they are suitable for use in household appliances and distribution boards in office and residential areas. They can also be used for applications where there is little space such as air conditioners, heating systems, pumps and fans, i. e. for simple electrical controls.

AC and DC operation

EN 60947-1, EN 60947-4-1

Surge suppression

The 3TG10 power relays/miniature contactors have an integrated protective circuit against opening surges.

Overload and short-circuit protection

The 3UA7 overload relay can be used for overload protection. This applies to mounting onto contactors and to stand-alone installation.

Information about short-circuit protection for the contactors can be found in the "Technical specifications" (see note on Technical Information on page 3/1).

Selection and ordering data

Rated data Utilization category AC-1 Switching of resistive loads at 55 °C	AC-2 and AC-3		Main contacts	Rated control supply voltage U_s	DT	Order No.	Price per PU	PU (UNIT, SET, M)	PS*	PG	Weight per PU approx.	
Operational current I_e up to 400 V	Power of AC loads at 50 Hz and 400 V	Operational current I_e up to 400 V ¹⁾	Power of AC loads at 50 Hz and 400 V	Version								
A	kW	A	kW	NO NC V							kg	
4-pole · Hum-free · With screw terminals												
For screw and snap-on mounting onto TH 35 standard mounting rail												
AC operation, 45 ... 450 Hz												
20	13	8.4	4	4	--	24 AC 110 AC 230 AC	▶	3TG10 10-0AC2	1	1 unit	101	0.157
				3	1	24 AC 110 AC 230 AC	▶	3TG10 10-0AG2	1	1 unit	101	0.158
						▶	3TG10 10-0AL2	1	1 unit	101	0.156	
						▶	3TG10 01-0AC2	1	1 unit	101	0.157	
						▶	3TG10 01-0AG2	1	1 unit	101	0.158	
						▶	3TG10 01-0AL2	1	1 unit	101	0.157	
DC operation												
3TG10 ...-0...	20	13	8.4	4	4	24 DC	▶	3TG10 10-0BB4	1	1 unit	101	0.157
				3	1	24 DC	▶	3TG10 01-0BB4	1	1 unit	101	0.157
4-pole · Hum-free · With 6.3 mm × 0.8 mm flat connectors												
For screw and snap-on mounting onto TH 35 standard mounting rail												
AC operation, 45 ... 450 Hz												
16	10	8.4	4	4	--	24 AC 110 AC 230 AC	▶	3TG10 10-1AC2	1	1 unit	101	0.146
				3	1	24 AC 110 AC 230 AC	▶	3TG10 10-1AG2	1	1 unit	101	0.146
						▶	3TG10 10-1AL2	1	1 unit	101	0.145	
						▶	3TG10 01-1AC2	1	1 unit	101	0.147	
						▶	3TG10 01-1AG2	1	1 unit	101	0.146	
						▶	3TG10 01-1AL2	1	1 unit	101	0.144	
DC operation												
3TG10 ...-1...	16	10	8.4	4	4	24 DC	C	3TG10 10-1BB4	1	1 unit	101	0.146
			8.4	4	3	24 DC	D	3TG10 01-1BB4	1	1 unit	101	0.146

For accessories see page 3/123.